

Maximum Total Current Draw per Phase	16A
Output Connections	(1) Hard Wire 3-wire (H N + G) (1) IEC Jumpers
Overload Protection	Yes
Cord Length	1 meters
Input	
Nominal Input Voltage	230V
Input Frequency	50/60 Hz
Acceptable Input Voltage	220-240 VAC
Maximum Line Current per phase	16A
Maximum Input Current per phase	16A
Load Capacity	3000 VA
Load Power Factor Range	0 to 1
Physical	
Net Weight	2.27 KG
Maximum Height	89.00 mm
Maximum Width	432.00 mm
Maximum Depth	76.00 mm
Shipping Weight	3.45 KG
Shipping Height	151.00 mm
Shipping Width	463.00 mm
Shipping Depth	295.00 mm
Color	Black
Units per Pallet	56.00
Environmental	
Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-4500 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Conformance	
Regulatory Approvals	VDE
Standard Warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
REACH	REACH: Contains No SVHCs