## 2-1747277-3 ACTIVE

### Dynamic Series | Dynamic 4000 Series

TE Internal #: 2-1747277-3

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 6.35 mm [. 249 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder,

Dynamic 4000 Series

View on TE.com >





Connectors > PCB Connectors > PCB Headers & Receptacles > Header Assembly: Wire-to-Board, 24A, Gold Plated











PCB Connector Assembly Type: PCB Mount Header

Connector System: Wire-to-Board

Number of Positions: 3

Number of Rows: 1

Centerline (Pitch): 6.35 mm [ .249 in ]

All Header Assembly: Wire-to-Board, 24A, Gold Plated (20)

### **Features**

### **Product Type Features**

PCB Connector Assembly Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	3
Number of Rows	1
PCB Mount Orientation	Vertical
Body Features	
Primary Product Color	Black



PCB Contact Termination Area Plating Material Thickness	2 μm[78.74 μin]
Contact Underplating Material Thickness	1.27 μm[50 μin]
Contact Mating Area Plating Material Thickness	.38 μm[15 μin]
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Type	Pin
Contact Current Rating (Max)	23 A
Termination Features	
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Retention	With
PCB Mount Retention Type	Retention Leg
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	With
Housing Features	
Housing Material	Polyester GF
Centerline (Pitch)	6.35 mm[.249 in]
Usage Conditions	
Operating Temperature (Max)	105 °C[221 °F]
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	16
Packaging Method	Tube



### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



Also in the Series | Dynamic 4000 Series





Connector Contacts(17)



Connector Hardware(2)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(20)



PCB Terminal Blocks(2)



Wire-to-Board Connector Assemblies & Housings(29)

### Customers Also Bought



TE Part #115607J001 Versafit-V2 Heat Shrink Tubing



TE Part #1-1318119-3
DYNAMIC D-2100 REC HSG 6P



TE Part #1827538-1
DYNAMIC 2000 HDR ASSY



TE Part #4-179555-3

DYNAMIC D-3200 WTW TAB HSG 6P



DYNAMIC D1000 REC CONT M GOLD 0.76 L/P



### **Documents**

### **Product Drawings**

DYNAMIC D4200 V-HDR ASSY 3P/Y

English

#### **CAD Files**

3D PDF

English

Customer View Model

ENG\_CVM\_2-1747277-3\_O2.3d\_igs.zip

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 6.35 mm [.249 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 4000 Series



English

**Customer View Model** 

ENG\_CVM\_2-1747277-3\_O2.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_2-1747277-3\_O2.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English

**Agency Approvals** 

**TUV Certificate** 

English