

GCJ31MR71H334KA01#

" # " indicates a package specification code.

Recommended

Reflow OK

Complies with RoHS

AEC-Q200

Fail safe

Deflecting crack

< List of part numbers with package codes >
GCJ31MR71H334KA01L , GCJ31MR71H334KA01K , GCJ31MR71H334KA01B

Shape



L size	3.2 ± 0.3mm
W size	1.6 ± 0.3mm
T size	1.15 ± 0.2mm
External terminal width e	0.3 to 1.0mm
Distance between external terminals g (Min.)	1.5mm
Size code in mm(inch)	3216 (1206)

References

Packaging	Specifications	Minimum quantity
L	Embossed tape (φ 180mm)	3000
K	Embossed tape (φ 330mm)	10000
B	Packing in bulk	1000

Mass (typ.)	
1 piece	34mg
Reel (φ 180mm)	149g

Specifications

Capacitance	0.33μF ± 10%
Rated voltage	50Vdc
Temperature characteristics (complied standard)	X7R(EIA)
Capacitance change rate	± 15%
Temperature range of temperature characteristics	-55 to 125
Operating temperature range	-55 to 125

 Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.