

## AMP | AMP CPC

TE Internal #: 206404-2

Connector Assembly, 250 VDC, Wire-to-Panel / Wire-to-Wire, 16 Position, Sealable, Wire & Cable, Receptacle, Pin, AMP CPC,


Circular Power Connectors

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors











Connector Product Type: Connector Assembly

Operating Voltage: 250 VDC

Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 16

Sealable: Yes

### **Features**

# **Product Type Features**

| Connector Product Type            | Connector Assembly          |
|-----------------------------------|-----------------------------|
| Connector System                  | Wire-to-Panel, Wire-to-Wire |
| Sealable                          | Yes                         |
| Connector & Contact Terminates To | Wire & Cable                |
| Connector & Housing Type          | Receptacle                  |
| Circular Connector Shell Type     | All Plastic                 |
| Configuration Features            |                             |
| Number of Positions               | 16                          |
| Number of Power Positions         | O                           |
| Number of Signal Positions        | 16                          |
| Electrical Characteristics        |                             |
| Operating Voltage                 | 250 VAC                     |
| Contact Features                  |                             |

No

Reverse Gender



| Contact Type                       | Pin                        |
|------------------------------------|----------------------------|
| Contact Current Rating (Max)       | 13 A                       |
| Contact Protection                 | With                       |
| Termination Features               |                            |
| Termination Method to Wire & Cable | Solder                     |
| Mechanical Attachment              |                            |
| Mating Alignment Type              | Keyed                      |
| Mating Alignment                   | With                       |
| Panel Mount Feature Type           | Flange with Mounting Holes |
| Mating Retention Type              | Threaded Coupling          |
| Connector Mounting Type            | Panel Mount                |
| Mating Retention                   | With                       |
| Panel Mount Feature                | With                       |
| Housing Features                   |                            |
| Housing Color                      | Black                      |
| Housing Material                   | PA 6.6 GF                  |
| Circular Connector Shell Size      | 17                         |
| Dimensions                         |                            |
|                                    | 1.76 in                    |
| Usage Conditions                   |                            |
| Operating Temperature Range        | -55 – 105 °C[-67 – 221 °F] |
| Fluid Resistance                   | None                       |
| Operation/Application              |                            |
| Circuit Application                | Signal                     |
| Shielded                           | No                         |
| Industry Standards                 |                            |
| UL Flammability Rating             | UL 94V-0                   |
| Packaging Features                 |                            |
| Packaging Quantity                 | 24                         |
| Packaging Method                   | Standard                   |
|                                    |                            |



# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Not Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold  |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (13% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content                               | BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.  |
| Solder Process Capability                     | Not applicable for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**






Also in the Series | AMP CPC






Circular Power Connectors(458)







Connector Caps & Covers(19)

Connector Contacts(6)



Connector Hardware(12)



Connector Seals & Cavity Plugs(36)



Connector Strain Relief(60)




Insertion & Extraction Tools(1)



# Customers Also Bought





## **Documents**

**Product Drawings** 

**CPC RECPT ASSEMBLY SIZE 17-16** 

English

**CAD Files** 

Customer View Model ENG\_CVM\_206404-2\_C.3d\_igs.zip

English



**Customer View Model** 

ENG\_CVM\_206404-2\_C.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_206404-2\_C.2d\_dxf.zip

English

3D PDF

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_206404-2\_M.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_206404-2\_M.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_206404-2\_M.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Product Specifications**

**Application Specification** 

English

**Agency Approvals** 

**UL Report** 

English