


HBL7594 -- Twist-Lock Plug



2P3W, 15A 125V, ML-2P, Nylon Cover, Phenolic Body, Black

Product Specifications

| | |
|-------------------------------------|---|
| Product Type | <p>Twist-Lock Devices</p> |
| Product Item | Plug |
| Wiring Scheme | 2-Pole, 3-Wire Grounding |
| Amperage | 15A |
| Voltage | 125V AC |
| NEMA Configuration | ML-2P |
| Item Style | Standard |
| Device Color | Black |
| Cord Dia. | .281"-.421" (7.1-10.7) |
| Blade Holder Material | Black Phenolic |
| Housing Material | Black Phenolic |
| Cord Clamp Material | Metallic |
| Blade Material | Brass |
| Terminal Clamp Material | Cold rolled steel-nickel-plated |
| Terminal Screw Material | #8-32 Brass |
| Ground Screw Material | Brass (green finish) |
| Cord Clamp Screw Material | Steel-zinc-plated |
| Body Holding Screw Material | Steel-zinc-plated |
| Ratings | Molded In or Stamped On |
| Catalog No | Permanently ink marked on product |
| Dielectric Voltage Withstand | 2000V minimum |
| Current Interrupting | Certified for current interrupting at full rated current |
| Temperature Rise | Max 30C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of .75. |
| Cord Accommodation | Round portable service cords of diameters commensurate with the device rating as defined in UL Standard 62, CSA C22.2 No. 49. |
| Terminal Accommodation | 15A #14 AWG |
| Terminal Identification | Terminals identified in accordance with UL 498 (X, Y, Z, White, Green) |
| Flammability | HB or better per UL 94 or CSA 22.2 No. 0.6 |
| Operating Temperatures | Maximum Continuous 75 C Minimum -40 C (w/o impact) |
| Moisture Resistance | IP20 |
| Listings | UL/CSA |
| UPC Number | 783585237770 |
| Weight in LBs | 0.1 |
| Link to Drawing Library | Click here for Library |
| Link to PDF Catalog | Click here for Catalog |



NEMA Configuration

