

SD-WMS 5 (NU)R YE - Conductor marking collar



0825942

<https://www.phoenixcontact.com/us/products/0825942>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Conductor marking collar, yellow, labeled, horizontal: Numbers, mounting type: thread on, cable diameter range: 2.5 ... 5 mm, lettering field size: 3.2 x 2.6 mm

Your advantages

- Easy and reliable conductor labeling with SD-WMS ... conductor marking collars
- Supplied in rolls
- Multi-character labels can be created by combining several pre-labeled individual collars

Commercial data

Item number	0825942
Packing unit	500 pc
Minimum order quantity	500 pc
Sales key	NULL
Product key	BG2221
Catalog page	Page 185 (CL2-2011)
Weight per piece (including packing)	0.081 g
Weight per piece (excluding packing)	0.046 g
Customs tariff number	49119900
Country of origin	SE

SD-WMS 5 (NU)R YE - Conductor marking collar



0825942

<https://www.phoenixcontact.com/us/products/0825942>

Technical data

Product properties

Product type	Labeled conductor marker
Type	Profile

Marking

Printing direction	horizontal
Printing	Numbers

Mounting

Mounting type	thread on
---------------	-----------

Material specifications

Color	yellow
Material	Polyvinyl chloride
Flammability rating according to UL 94	V0
Components	Free from silicone and cadmium

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesa film test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h
Specification	IEC 60068-2-2:2007-07
Result	Test passed
Duration	96 h
Temperature for testing	105 °C

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 80 °C (105 °C)	Test passed

SD-WMS 5 (NU)R YE - Conductor marking collar



0825942

<https://www.phoenixcontact.com/us/products/0825942>

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Specification	ISO 175:2010 (following)
Test duration	168 h
Sodium hydroxide 0.1 mol/l [CAS No. 1310-73-2]	Test passed
Ethanol (99 %) [CAS No. 64-17-5]	Test passed
Diesel [CAS No. 68476-34-6]	Test passed
IRM 901	Test passed
IRM 902	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-30 °C ... 60 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	1 Year

Dimensions

Width	3.2 mm
Height	5.5 mm
Length	4.2 mm

External dimensions

SD-WMS 5 (NU)R YE - Conductor marking collar



0825942

<https://www.phoenixcontact.com/us/products/0825942>

Outside diameter	2.5 mm ... 5 mm
------------------	-----------------

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Notes

General	Please specify the required marking with order: Minimum order per imprint: 1 packing unit
---------	---

SD-WMS 5 (NU)R YE - Conductor marking collar



0825942

<https://www.phoenixcontact.com/us/products/0825942>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

SD-WMS 5 (NU)R YE - Conductor marking collar



0825942

<https://www.phoenixcontact.com/us/products/0825942>

Accessories

SD-WMS 5 TOOL - Alignment tool for cable markers

0826475

<https://www.phoenixcontact.com/us/products/0826475>



Alignment tool for cable markers, Bare metallic, mounting type: thread on, cable diameter range: 2.5 ... 5 mm

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com