

CHAMP

TE Internal #: 5552235-1

Receptacle, Cable-to-Board, 36 Position, 2.16 mm [.085 in]


Centerline, 2 Row, Standard Profile, Vertical, Mating Retention, PCB

D-Sub Connectors

View on TE.com >



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Receptacle Assembly: Vertical, 2.16mm



Connector & Housing Type: Receptacle

Connector System: Cable-to-Board

Number of Positions: 36

Centerline (Pitch): 2.16 mm [.085 in]

Number of Rows: 2

All D-Sub Receptacle Assembly: Vertical, 2.16mm (5)

Features

Product Type Features

Contact Options

Contact Mating Area Plating Material

PCB Contact Termination Area Plating Material

Contact Underplating Material

Contact Base Material

Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	36
Number of Rows	2
PCB Mount Orientation	Vertical
Body Features	
Primary Product Color	Black
Connector Profile	Standard
Contact Features	

Installed

Gold, Gold Flash

Palladium Nickel

Phosphor Bronze

30 µin

Tin



Termination Features

Rectangular Termination Post & Tail Thickness	.25 mm[.01 in]
Rectangular Termination Post & Tail Width	.5 mm[.019 in]
Termination Post & Tail Length	.18 mm
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mounting Feature Material	Thermoplastic
PCB Mount Retention	Without
Mating Retention	With
Mating Retention Type	Bail Lock, Screwlocks
Connector Mounting Type	Board Mount

Housing Features

Housing Material	Thermoplastic
Centerline (Pitch)	2.16 mm[.085 in]

Dimensions

PCB Thickness (Recommended)	1.57 mm, 2.36 mm, 3.18 mm[.062 in][.093 in] [.125 in]
Row-to-Row Spacing	4.3 mm[.169 in]

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]

Operation/Application

Shielded	No
Circuit Application	Signal

Industry Standards

UL Flammability Rating UL 94V-0	- Flammability Rating	UL 94V-0	
---------------------------------	-----------------------	----------	--

Packaging Features

Packaging Quantity	75
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Customers Also Bought















TE Part #T4171110405-002 M12,REAR MOUNTING,FEMALE,B,5P, 0.5M WIRE

Documents

Product Drawings
ASSY, RCPT, 36 POS, VERT MTG



English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_5552235-1_O.2d_dxf.zip

English

Customer View Model

ENG_CVM_5552235-1_O.3d_igs.zip

English

Customer View Model

ENG_CVM_5552235-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English