

SACC-AT04-4P-RS-IV - Connector housing



1520951

<https://www.phoenixcontact.com/us/products/1520951>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Connector housing, Crimp contacts

Commercial data

Item number	1520951
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BF72
Product key	BF2IEA
GTIN	4063151985035
Weight per piece (including packing)	22.22 g
Weight per piece (excluding packing)	7 g
Country of origin	MX

SACC-AT04-4P-RS-IV - Connector housing



1520951

<https://www.phoenixcontact.com/us/products/1520951>

Technical data

Notes

General	AT04-4P-RD01BLK
General	Use with Size 16 pin contacts

Trade restriction

CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
---------	--

Product properties

Product type	Contact insert
Series	AT04
Contact numbering	1 - 4
Shielded	no

Data management status

Article revision	00
------------------	----


Electrical properties

Specific dielectric strength	1500 V AC (Less than 2 mA current leakage)
Insulation resistance	1000 MΩ (at 25 °C)

Connection data

Connection method	Crimp contacts
-------------------	----------------

Dimensions

Dimensional drawing	
Width	21 mm
Height	19.6 mm
Length	46.2 mm

Material specifications

Seal material Profile gasket	Silicon
Seal material Cable seal	Silicon
Housing material	PA-GF

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	-------

Characteristics

SACC-AT04-4P-RS-IV - Connector housing



1520951

<https://www.phoenixcontact.com/us/products/1520951>

Specific dielectric strength	1500 V AC (Less than 2 mA current leakage)
------------------------------	--

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP68 (in mated condition)
	IP69K (in mated condition)
Ambient temperature (operation)	-55 °C ... 125 °C


SACC-AT04-4P-RS-IV - Connector housing

1520951

<https://www.phoenixcontact.com/us/products/1520951>


Drawings

Dimensional drawing



AT04-4P top view and side view

Schematic diagram



AT04-4P pin assignment

SACC-AT04-4P-RS-IV - Connector housing



1520951

<https://www.phoenixcontact.com/us/products/1520951>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

SACC-AT04-4P-RS-IV - Connector housing



1520951

<https://www.phoenixcontact.com/us/products/1520951>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

SACC-AT04-4P-RS-IV - Connector housing



1520951

<https://www.phoenixcontact.com/us/products/1520951>

Accessories

CC-AT60-S16-R14-NI - Crimp contact

1519754

<https://www.phoenixcontact.com/us/products/1519754>



Crimp contact, contact diameter: 1.6 mm, turned, Pin, contact material: Copper alloy, contact surface: nickel-plated, connection cross section: 2.5 mm² ... 2.5 mm², AWG 14 ... 14

CC-AT60-S16-R16/20-AU - Crimp contact

1519755

<https://www.phoenixcontact.com/us/products/1519755>



Crimp contact, contact diameter: 1.6 mm, turned, Pin, contact material: Copper alloy, contact surface: gold-plated, connection cross section: 0.5 mm² ... 1.5 mm², AWG 20 ... 16

SACC-AT04-4P-RS-IV - Connector housing



1520951

<https://www.phoenixcontact.com/us/products/1520951>

CC-AT60-S16-R16/20-NI - Crimp contact

1519756

<https://www.phoenixcontact.com/us/products/1519756>




Crimp contact, contact diameter: 1.6 mm, turned, Pin, contact material: Copper alloy, contact surface: nickel-plated, connection cross section: 0.5 mm² ... 1.5 mm², AWG 20 ... 16

IV-AW4P - Terminal position assurance

1521030

<https://www.phoenixcontact.com/us/products/1521030>



Terminal position assurance, number of positions: 4, material: PA-GF

SACC-AT04-4P-RS-IV - Connector housing

1520951

<https://www.phoenixcontact.com/us/products/1520951>



IV-SP16 - Filler plug

1521037

<https://www.phoenixcontact.com/us/products/1521037>



Filler plug

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com