

Part Number: 1200878513

Product Description: Nano-Change (M8) to Micro-Change (M12) Double-Ended Cordset, 3 Poles, Female (90°) to Male (Straight), 0.25mm<sup>2</sup> PUR LS0H Cable, 1.0m (3.28') Length

Status: Active

Engineering Number: 483031H08M010

Series Number: 120087

**Product Category:** Circular Industrial

Cordsets

#### **Documents & Resources**

#### **Drawings**

Drawing 1200878513\_sd.pdf

## **Product Environment Compliance**

### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### **EU RoHS Certificate of Compliance**

#### **Part Details**

#### General

Status	Active
--------	--------

Category	Circular Industrial Cordsets
Series	120087
Description	Nano-Change (M8) to Micro- Change (M12) Double-Ended Cordset, 3 Poles, Female (90°) to Male (Straight), 0.25mm <sup>2</sup> PUR LS0H Cable, 1.0m (3.28') Length
IP Rating	IP68
Product Family	Brad Nano-Change (M8) Products
Product Name	Micro-Change (M12),Nano-Change (M8)
Protocol	N/A
Region	Europe
Туре	Double Ended
UPC	78172532395

# Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	60V AC / 75V DC

# Physical

Cable Diameter	N/A
Cable Diameter	IN/A
Cable Length	1.0m (3.28')
Color - Cable Jacket	Black
Connector End A	Nano-Change (M8)
Connector End B	Micro-Change (M12)
Coupling Style	Threaded
Gender	Female-Male
Keyway	None
LED Indicator	No
Material - Cable Jacket	PUR
Material - Connector Body	TPE
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Orientation	90° to Straight

Poles	3
Temperature Range - Operating	-25° to +80°C
Wire/Cable Type	UL 21198
Wire Size (AWG)	N/A

This document was generated on Sep 16, 2024