



# Instant Super Degreaser



## FEATURES

- Heavy-duty action removes oil, grease, wax, dirt, moisture, tar, and other contaminants
- Heavy-duty performance
- Power blast spray
- Removes oil, grease, dirt and tar
- Non-flammable, and non-conductive
- Does not contain chlorinated solvents
- Fast evaporating
- No rinsing, no residue
- Safe on most metals

## APPLICATIONS

- Air Compressors
- Bearings
- Cables
- Chains
- Forklifts
- Gears
- Heavy Equipment
- Power Tools

## SPECIFICATIONS AND APPROVALS

- Kimberly-Clark
- NSF International, C1
- Canadian Food Inspection Agency
- McDonnell Douglas CSD #1
- Boeing D6-17487 Rev. P
- Airbus ABR 9-0140 Issue 5A Type I

## PROPERTIES

<b>Appearance/physical state</b>	Gas/Aerosol
<b>Odor</b>	Strong
<b>Melting point/freezing point</b>	-166 °F (-110 °C) (estimated based on nPB)
<b>Boiling point/range</b>	158°F (70 °C)
<b>Vapor pressure</b>	134 mm Hg @ 25°C
<b>Partition coefficient</b>	Not available
<b>Percent volatile</b>	100%
<b>Flammability limit</b>	Flammability limit - lower (%) 3.8 % Flammability limit - upper (%) 9.5 %
<b>Propellant</b>	Carbon dioxide
<b>VOC Content</b>	96.5% per US State and Federal Consumer Product Regulations
<b>Color</b>	Colorless to light yellow
<b>Flash point</b>	None. ASTM D-56 TCC (Liquid portion)
<b>Relative density</b>	Not available
<b>Evaporation rate</b>	4.7
<b>Vapor density</b>	4.24 (estimated based on nPB)
<b>Auto-ignition temperature</b>	> 914°F (>490°C) (estimated based on nPB)
<b>Viscosity</b>	Not available
<b>Specific Gravity (water=1)</b>	1.34 - 1.36
<b>Temperature Range °F(°C)</b>	Not applicable
<b>4-Ball Weld Load</b>	Not applicable

## DIRECTIONS

Spray on parts and equipment. Allow flushing action to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

## HANDLING

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. (see Section 7 of the SDS)

## STORAGE

Store locked up. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. (see Section 7 of the SDS)

## DISPOSAL INFORMATION

Contents under pressure. Do not puncture, incinerate or crush. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

## AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Case Weight
	Canada	Europe				
00755 (min qty req)	N/A		55 gal	drum	1	
00720	C00720		20 wt oz / 567 g / 441 mL	aerosol	12	19 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | [www.itwprobrands.com](http://www.itwprobrands.com)

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved