



140×140×38 mm

San Ace 140W 9WL type 

General Specifications

- Material Frame: Aluminum (Black coating), Impeller: Plastic (Flammability: UL 94V-0)
- Expected life See the table below. (L10 life: 90% survival rate for continuous operation in indoor free air at 60°C, rated voltage)
- Motor protection function Locked rotor burnout protection, Reverse polarity protection
For details, please refer to p. 529.
- Dielectric strength 50/60 Hz, 500 VAC, for 1 minute (between lead wire conductors and frame)
- Insulation resistance 10 MΩ or more with a 500 VDC megger (between lead wire conductors and frame)
- Sound pressure level (SPL) At 1 m away from the air inlet
- Storage temperature -30 to +70°C (Non-condensing)
- Lead wire ⊕Red ⊖Black Sensor Yellow Control Brown
- Mass 740 g
- Ingress protection IP68

Specifications

The models listed below **have pulse sensors with PWM control function.**

Model no.	Rated voltage [V]	Operating voltage range [V]	PWM duty cycle* [%]	Rated current [A]	Rated input [W]	Rated speed [min ⁻¹]	Max. airflow [m³/min] [CFM]		Max. static pressure [Pa] [inchH ₂ O]		SPL [dB (A)]	Operating temperature [°C]	Expected life [h]
9WL1412P1A001	12	10.2 to 13.8	100	3.72	44.64	6900	8.0	282	516	2.07	68	-20 to +70	100000/60°C
20			0.27	3.24	2300	2.66	93	80	0.32	39			
9WL1412P1H001			100	1.7	20.4	5200	6.0	212	300	1.2	62		
20			0.27	3.24	2300	2.66	93	80	0.32	39			
9WL1412P1M001			100	0.6	7.2	3300	3.7	130	170	0.68	46		
20	0.16	1.92	1300	1.45	51	26	0.1	29					
9WL1424P1A001	24	20.4 to 27.6	100	1.86	44.64	6900	8.0	282	516	2.07	68		
20			0.17	4.08	2300	2.66	93	80	0.32	39			
9WL1424P1H001			100	0.85	20.4	5200	6.0	212	300	1.2	62		
20			0.16	3.84	2300	2.66	93	80	0.32	39			
9WL1424P1M001			100	0.3	7.2	3300	3.7	130	170	0.68	46		
20	0.11	2.64	1300	1.45	51	26	0.1	29					
9WL1448P1A001	48	40.8 to 55.2	100	0.92	44.16	6900	8.0	282	516	2.07	68		
20			0.11	5.28	2300	2.66	93	80	0.32	39			
9WL1448P1H001			100	0.42	20.16	5200	6.0	212	300	1.2	62		
20			0.11	5.28	2300	2.66	93	80	0.32	39			
9WL1448P1M001			100	0.15	7.2	3300	3.7	130	170	0.68	46		
20	0.09	4.32	1300	1.45	51	26	0.1	29					

* PWM frequency: 25 kHz. Fan does not rotate when PWM duty cycle is 0%.

Other sensor specifications are available as options. Refer to the index (p. 559).




Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9WL1412P1A001 With pulse sensor with PWM control function

PWM duty cycle

Operating voltage range


PWM duty - Speed characteristics example




Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9WL1412P1H001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9WL1412P1M001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9WL1424P1A001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9WL1424P1H001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range



PWM duty - Speed characteristics example




DC

Splash Proof Fan 140 mm sq.


Airflow - Static Pressure Characteristics / PWM Duty - Speed Characteristics Example

9WL1424P1M001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9WL1448P1A001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9WL1448P1H001 With pulse sensor with PWM control function


PWM duty cycle



Operating voltage range




PWM duty - Speed characteristics example




9WL1448P1M001 With pulse sensor with PWM control function


PWM duty cycle




Operating voltage range




PWM duty - Speed characteristics example



Dimensions (unit: mm)



Reference Dimensions of Mounting Holes and Vent Opening (unit: mm)



Options

Finger guards

page: p. 514

Model no.: 109-719, 109-719H

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Sanyo Denki:

[9WL1424P1A001](#) [9WL1412P1M001](#) [9WL1448P1H001](#) [9WL1448P1M001](#) [9WL1424P1M001](#) [9WL1424P1H001](#)
[9WL1448P1A001](#) [9WL1412P1A001](#) [9WL1412P1H001](#) [9WL1412M1001](#) [9WL1424M1001](#) [9WL1448M1001](#)
[9WL1412M1002](#) [9WL1448M1002](#) [9WL1448M1D001](#) [9WL1424M1002](#) [9WL1412M1D001](#)