


Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

TO
PCK




RECOMMENDED LAND PATTERN DIMENSION OF PCB


- NOTES
- 12 HATCHED  PARTS:GROUND CIRCUIT.
 - 2 HATCHED  PARTS:GROUND CIRCUIT.
 - SMT LEAD-COPLANARITY:0.1 MAX.
 - THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
 - THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE

CROSS CUT SECTION - SIGNAL (5 : 1)



CROSS CUT SECTION - GROUND (5 : 1)



1	LCP	BEIGE	UL94V-0	3, 4	PHOSPHOR BRONZE	TIN-PLATING
NO.	MATERIAL	FINISH, REMARKS		2	PHOSPHOR BRONZE	CONTACT AREA : GOLD 0.1μ m min. LEAD AREA : GOLD FLASH UNDER PLATING : NICKEL 1μ m min.
CODE NO. (OLD) CL	DRAWN A.SUZUKAWA 06.06.02	DESIGNED H. Nakamura 06.06.05	CHECKED H. Ogasawara 06.06.05	APPROVED H. Ogasawara 06.06.06	RELEASED .	
SCALE 4 : 1	DRAWING NO. EDC3-151978-25	PART NO. FX10A-120S/12-SV(71)	CODE NO. CL570-0203-0-71			
UNITS mm	HIROSE ELECTRIC CO., LTD					