

# HC-M-04-PT-M - Contact insert module



1424221

<https://www.phoenixcontact.com/us/products/1424221>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 4, power contacts: 4, control contacts: 0, Pin, Push-in connection, 830 V, 40 A, 2.5 mm<sup>2</sup> ... 6 mm<sup>2</sup>, application: Power

## Your advantages

- Easy installation without tools, even when mounted, with push-in connection technology
- Shortest installation time compared to other connection technologies
- Quick and effortless wiring, in particular when space is tight
- Automatic cabling with robots possible
- Safe wiring and operation with color-coded actuators
- Shock and vibration-resistant in accordance with DIN EN 61373

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1424221       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 1 pc          |
| Sales key                            | BF62          |
| Product key                          | BF7ACE        |
| GTIN                                 | 4055626369525 |
| Weight per piece (including packing) | 36.2 g        |
| Weight per piece (excluding packing) | 36 g          |
| Customs tariff number                | 85366990      |
| Country of origin                    | CN            |

# HC-M-04-PT-M - Contact insert module



1424221

<https://www.phoenixcontact.com/us/products/1424221>

## Technical data

### Notes

|         |                                                                               |
|---------|-------------------------------------------------------------------------------|
| General | for flexible conductors with or without ferrules                              |
| General | Connectors may be operated only when there is no load/voltage.                |
| General | For HEAVYCON housing type B6 ... B48 and module carrier frame HC-M-B...MF-... |

### Mounting

|               |                                                                                           |
|---------------|-------------------------------------------------------------------------------------------|
| Assembly note | To ensure correct use, installation in housing with IP54 protection or better is required |
|---------------|-------------------------------------------------------------------------------------------|

### Product properties

|                         |                        |
|-------------------------|------------------------|
| Product type            | Modular contact insert |
| Series                  | HC-M-04P               |
| Application             | Power                  |
| Number of positions     | 4                      |
| Connection profile      | 4                      |
| Number of module slots  | 1                      |
| No. of power contacts   | 4                      |
| No. of control contacts | 0                      |
| Contact material type   | rolled                 |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 01 |
|------------------|----|

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Connection data

#### Connection technology

|                                  |                    |
|----------------------------------|--------------------|
| Connection technology            | Push-in connection |
| Connection in acc. with standard | IEC / EN           |

#### Conductor connection

|                                         |                                           |
|-----------------------------------------|-------------------------------------------|
| Conductor cross section                 | 2.5 mm <sup>2</sup> ... 6 mm <sup>2</sup> |
| Connection cross section AWG            | 14 ... 10                                 |
| Stripping length of the individual wire | 9.6 mm                                    |

### Dimensions

#### Mechanical characteristics

|                        |       |
|------------------------|-------|
| Minimum housing height | 72 mm |
| Contact diameter       | 4 mm  |

# HC-M-04-PT-M - Contact insert module



1424221

<https://www.phoenixcontact.com/us/products/1424221>

## Electrical properties

|                                |        |
|--------------------------------|--------|
| Rated voltage (III/2) contacts | 1000 V |
| Rated voltage (III/3)          | 830 V  |
| Rated surge voltage (III/2)    | 8 kV   |
| Rated surge voltage (III/3)    | 8 kV   |
| Rated surge voltage            | 8 kV   |
| Rated current                  | 40 A   |

## Mechanical properties

### Mechanical data

|                             |       |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 500 |
|-----------------------------|-------|

## Material specifications

|                                        |                                                                                                                         |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Flammability rating according to UL 94 | V0                                                                                                                      |
| Contact material                       | Copper alloy                                                                                                            |
| Contact surface material               | Ag                                                                                                                      |
| Contact carrier material               | PC                                                                                                                      |
| Standards/regulations                  | PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3) |

## Environmental and real-life conditions

### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -40 °C ... 125 °C |
|---------------------------------|-------------------|


## Standards and regulations

### Testing

|                       |                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Standards/regulations | PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3) |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|


## Drawings

Diagram



Derating diagram for flexible conductors with ferrule

Diagram



Derating diagram for flexible conductors


# HC-M-04-PT-M - Contact insert module



1424221

<https://www.phoenixcontact.com/us/products/1424221>

Schematic diagram



Connector pin assignment, connection side


# HC-M-04-PT-M - Contact insert module



1424221

<https://www.phoenixcontact.com/us/products/1424221>

Dimensional drawing



Dimensional drawing

# HC-M-04-PT-M - Contact insert module



1424221

<https://www.phoenixcontact.com/us/products/1424221>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1424221>

|                                                                                   |                                                 |                                |                   |                               |
|-----------------------------------------------------------------------------------|-------------------------------------------------|--------------------------------|-------------------|-------------------------------|
|  | <b>cULus Recognized</b><br>Approval ID: E468743 |                                |                   |                               |
|                                                                                   | Nominal voltage U <sub>N</sub>                  | Nominal current I <sub>N</sub> | Cross section AWG | Cross section mm <sup>2</sup> |
|                                                                                   | 600 V                                           | 30 A                           | - 10              | -                             |

# HC-M-04-PT-M - Contact insert module



1424221

<https://www.phoenixcontact.com/us/products/1424221>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440217 |
| ECLASS-12.0 | 27440217 |
| ECLASS-13.0 | 27440217 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000438 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# HC-M-04-PT-M - Contact insert module



1424221  
<https://www.phoenixcontact.com/us/products/1424221>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)