# 5-1761184-1 ACTIVE

#### **AMPLIMITE**

TE Internal #: 5-1761184-1

Plug, Flat Ribbon Cable, 24 AWG Wire Size, .2 mm² / .205 mm²

Wire Size, Cable-to-Board, 4 Position, 1.27 mm [.05 in] Centerline,

SDL Connectors

View on TE.com >



Connectors > Audio & Video Connectors > SDL Connectors











Connector & Housing Type: Plug

Compatible With Wire & Cable Type: Flat Ribbon Cable

Wire Size: .2 mm², .205 mm²

Connector System: Cable-to-Board

## **Features**

## **Product Type Features**

Receptacle Configuration	Standard
Connector & Housing Type	Plug
Connector System	Cable-to-Board
Connector & Contact Terminates To	Wire & Cable

## **Configuration Features**

Compatible With Wire & Cable Type	Flat Ribbon Cable
Number of Positions	4

### **Body Features**

Shield Plating Material	Tin over Nickel
Shield Material	Brass

#### **Contact Features**

	50 μin
Contact Mating Area Plating Material	Gold
Contact Base Material	Copper Alloy



Contact Current Rating (Max)	1.5 A
------------------------------	-------

#### Mechanical Attachment

PCB Mount Retention	Without
Polarization Code	E
Connector Mounting Type	Cable Mount (Free-Hanging)

#### **Housing Features**

Housing Material	Polycarbonate GF
Housing Color	Smoke Gray
Centerline (Pitch)	1.27 mm[.05 in]

#### **Dimensions**

Conductor Insulation Diameter Range	1.27 mm[.05 in]
Wire Size	.2 mm², .205 mm²

## **Usage Conditions**

Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]

### Operation/Application

Circuit Application	Signal	
	$\sim$	

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products


Plug, Flat Ribbon Cable, 24 AWG Wire Size, .2 mm² / .205 mm² Wire Size, Cable-to-Board, 4 Position, 1.27 mm [.05 in] Centerline, SDL Connectors



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts





## Customers Also Bought





#### **Documents**

Product Drawings
4 SDL FLAT PLUG ASSY

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_5-1761184-1\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1761184-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-1761184-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Plug, Flat Ribbon Cable, 24 AWG Wire Size, .2 mm² / .205 mm² Wire Size, Cable-to-Board, 4 Position, 1.27 mm [.05 in] Centerline, SDL Connectors



**Product Specifications** 

**Application Specification** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

English