tyco Electronics

Sign In

Search By: Part Number   Text   Tips

Enter a complete or partial part number...   Go

**Products**   **Documentation**   **Resources**   **My Account**   **Customer Support**   **About Us**

Home > Products > By Type > Ribbon and Flat Flex Wire Connectors - Ribbon Cable > Product Feature Selector > Product Details

Product Details for 1437064-3

1437064-3

✔ Active

Pin and Pinless Headers (AMP-LATCH)

5 of 6 RoHS/ELV Compliant   (Find RoHS Compliant Alternates/Compliance Statement)

Product Highlights:
- Connector Type = Pin Headers
- Low Profile
- Number of Positions = 26
- 2.54 x 2.54 mm Centerline, Matrix
- PCB Mount Angle = Vertical

View all Features

Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product

Documentation & Additional Information

Product Drawings:
- VERTICAL EJECTOR HEADER (PDF, English)

Catalog Pages/Data Sheets:
- None Available

Product Specifications:
- None Available

Application Specifications:
- None Available

Instruction Sheets:
- None Available

CAD Files:
- None Available

Additional Information:
- Product Line Information

Related Products:
- Tooling

List all Documents

Product Features   (Please use the Product Drawing for all design activity)

Product Type Features:
- Connector Type = Pin Headers
- Profile = Low
- Number of Positions = 26
- PCB Mount Angle = Vertical
- PCB Retention Feature = Without
- Mating Polarization Method = Center, Dual Polarizing Bar
- Mating Connector Lock = Without
- Housing Style = 4-Sided
- Ejection Latches = With
- Post Size (mm [in]) = 0.64 [.025]
- Shrouded = Yes
- Mating Polarization = With
- Shrouded End Dimension (mm [in]) = 3.81 [0.150]

Termination Related Features:
- Termination Post Length (mm [in]) = 6.10 [0.240]

Body Related Features:
- Centerline, Matrix (mm [in]) = 2.54 x 2.54 [.100 x .100]
- Daisy Chain = With

Contact Related Features:
- Contact Mating Area Plating = Gold (30) over Nickel
- Contact Shape = Square
- Contact Material = Phosphor Bronze

Housing Related Features:
- Housing Material = Thermoplastic
- Housing Flammability Rating = UL 94V-0
- Housing Color = Blue

Industry Standards:
- RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Conditions for Usage:
- Temperature Rating = Standard

Other:
- Brand = AMP