REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE		
A1	N/A		图面升级整理图面	2024.08.28	阿树











Specifications:
规格：
Voltage rating:50V AC/DC
额定电压：50V AC/DC
Current rating:1A AC/DC
额定电流：1A AC/DC
Withstanding voltage:500V AC/minute
耐受电压：500V AC/分钟
Temperature range:−40℃~+125℃
温度范围：−40℃~+125℃
Insulation resistance:100MΩ min
绝缘电阻：100MΩ Min
Contact resistance:20mΩ Max
接触电阻：20mΩ Max

PART NO.:

X1011 H−2xXX−N0 HF
① ② ③ ④ ⑤

1.Series No
2.Category:H−HSG
3.Row No.Pin No:2x04~2x25
4.Material:N0−Nylon66 (White) UL 94V−0
5:HF−Halogen Free

Poles	Dimensions/mm		
	A	B	C
2x04	3.00	5.20	7.00
2x05	4.00	6.20	8.00
2x06	5.00	7.20	9.00
2x08	7.00	8.20	11.00
2x09	8.00	9.20	12.00
2x10	9.00	11.20	13.00
2x15	14.00	16.20	18.00
2x20	19.00	21.20	23.00
2x25	24.00	26.20	28.00

X1011H−2xXX−N0HF	Nylon66	X1011W	X1011T
PART NO	Material	Suitable XKB Wafer	Suitable XKB Terminal

ANGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERANCES	

XKB Connection

DESIGN	阿树	VIEW:	MODEL TYPE: 1.0mm Crimp Style Connector
CHECKED		UNIT: mm/in	PART NO.: X1011H−2xXX−N0HF
APPROVED		SIZE: A4	DWG NO.:

XKB INDUSTRIAL PRECISION CO.,LIMITED

SCALE	PAGE	REVISION
N/A	1/1	A1