



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.51 – 1.03 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Low
-----------------	-----

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
-----------------------------------	---------------

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable
-----------------------	--------------



Mechanical Attachment

Extraction Force	70 Newton
Locking Lance Height	.2 mm[.008 in]
Wire Insulation Support	With

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	19.58 mm[.77 in]
Compatible Insulation Diameter Range	2.01 – 2.7 mm[.079 – .106 in]
Wire Size	.51 – 1.03 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Packaging Features

Packaging Quantity	8000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as



EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 154717-1 PL 250 REC TERMINAL 13-11 AWG BR	 TE Part # 160759-1 PL 250 TERMINAL REC 0.5-1.5 MM2 BR	 TE Part # 170233-1 PL 250 REC 0.5-2.27 MM2 BR	 TE Part # 154718-1 250 PL MKI REC. 18-14AWG BR
 TE Part # 927852-1 PL 250 REC TERMINAL 20-17 AWG BR	 TE Part # 927852-2 PL 250 REC TERMINAL 20-17 AWG PBR	 TE Part # 926820-6 PL 250 FLAG REC 0.5-1.5 MM2 0.4X.44	 TE Part # 1380089-1 PL MKIII .250 REC 1.0-2.5MM2
 TE Part # 926820-5 PL 250 REC TERMINAL-FLAG 20-15 AWG BR	 TE Part # 880646-1 PL REC 0.5-1.0MM2 0.40 X 52.32 BR		

Also in the Series | Mark III

Crimp Terminal Housings(30)	Quick Disconnects(15)



Also in the Series

Positive Lock 250

Automotive Terminals(1)

Crimp Terminal Housings(190)

Insertion & Extraction Tools(3)

Insulation Boots & Sleeves(4)

Quick Disconnects(185)

Customers Also Bought

TE Part #2133857-5
250 FASTON HSG.,FLAG,REC.,1 POS, BLACK

TE Part #880688-1
FF 250 TERMINAL 0.5-1.0MM2 0.39 X13.2 BR

TE Part #4-280050-1
250 FASTON,FLAG,REC.,16-20 AWG, BR

TE Part #880683-2
FF 250 TERMINAL REC 0.5-1.0 MM2 TPBR

TE Part #626028-4
RING TONGUE TERMINAL

TE Part #735212-1
FF 250 REC 22-17AWG BR

TE Part #969184-1
AMVAR FF 250 REC DIA 0.9-1.6 PB

Documents

Product Drawings

PL MKIII .250 REC 0.5-1.0MM2

English

CAD Files

3D PDF

3D



Customer View Model

[ENG_CVM_CVM_1380088-1_D1.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1380088-1_D1.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1380088-1_D1.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Positive Lock MK III, .250 series](#)

English

Agency Approvals

[UL Report](#)

English