



Part Number : [2125161003](#)
Product Description : Mini-Fit Max Terminal
Position Assurance (TPA) Retainer, 4.20mm
Pitch, UL 94V-0, Glow-Wire Capable, 3 Circuit,
Natural
Series Number : 212516
Status : Active
Product Category : Connector Accessories



Documents & Resources


Drawings
[2125161003_sd.pdf](#)

3D Models and Design Files
[2125161003_stp.zip](#)

Specifications
[2125150000-PS-000.pdf](#)
[2125150000-TS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Connector Accessories
Series	212516
Description	Mini-Fit Max Terminal Position Assurance (TPA) Retainer, 4.20mm Pitch, UL 94V-0, Glow-Wire Capable, 3 Circuit, Natural
Component Type	Terminal Position Assurance
Product Name	Mini-Fit Max
UPC	193264598229

Physical

Circuits (Loaded)	3
Circuits (maximum)	3
Color - Resin	Natural
Material - Resin	Nylon
Net Weight	0.210/g
Number of Rows	1
Packaging Type	Bag
Temperature Range - Operating	-40° to +105°C

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Use with Part(s)

Description	Part Number
-------------	-------------

Mini-Fit Max Receptacle Housing, Dual Row, UL 94V-0, 6 Circuits, Glow-Wire Capable, Black	<u>2125141006</u>
---	-------------------

This document was generated on Oct 29, 2024