




**Part Number :** [152680357](#)  
**Product Description :** 1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 203.00mm Cable Length, Tin (Sn) Plating, 28 Circuits  
**Series Number :** 15268  
**Status :** Active  
**Product Category :** Flexible Printed Circuit (FPC) Flex Jumpers




Documents & Resources

Drawings  
[152680357\\_sd.pdf](#)

Specifications  
[PS-15268-001-001.pdf](#)

Product Environment Compliance

Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant  |
| China RoHS         |  |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21  |
| REACH SVHC         | Not Contained per D(2024)4144-DC (27 June 2024)                                       |
| EU RoHS            | Compliant per EU 2015/863   |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

## Part Details

### General

|              |   |
|--------------|---|
| Status       | Active  |
| Category     | Flexible Printed Circuit (FPC) Flex Jumpers   |
| Series       | 15268   |
| Description  | 1.25mm Pitch Premo-Flex FFC Jumper, Same Side Contacts (Type A), 203.00mm Cable Length, Tin (Sn) Plating, 28 Circuits |
| Comments     | Contacts on the same side, Type A   |
| Product Name | Premo-Flex FFC Jumper   |
| UPC          | 884982427402  |

### Agency

|    |        |
|----|--------|
| UL | E29179 |
|----|--------|

### Electrical

|                               |        |
|-------------------------------|--------|
| Current - Maximum per Contact | 1.4A   |
| Voltage - Maximum             | 60V AC |

### Physical

|                               |                |
|-------------------------------|----------------|
| Cable Length                  | 203.00mm       |
| Circuits (Loaded)             | 28             |
| Contact Layout Type           | A (same side)  |
| Design Feature                | Flexible       |
| Flammability                  | 94V-0          |
| Material - Plating Mating     | Tin            |
| Net Weight                    | 4.861/g        |
| Packaging Type                | Bag            |
| Pitch - Mating Interface      | 1.25mm         |
| Temperature Range - Operating | -40° to +105°C |
| Termination Style             | FFC Connector  |

|                 |                 |
|-----------------|-----------------|
| Wire/Cable Type | Flat Flex Cable |
| Wire Size (AWG) | N/A             |

---

**Mates With / Use With**

**Mates with Part(s)**

| Description  | Part Number     |
|--|-----------------|
| 1.25mm Pitch Easy-On FFC/FPC Connector, Through-Hole, Right-Angle, ZIF, Top Contact Style, 28 Circuits | <u>39532284</u> |
| 1.25mm Pitch Easy-On FFC/FPC Connector, Through-Hole, Vertical, ZIF, 28 Circuits                       | <u>39532285</u> |