




Connectors > PCB Connectors > PCB Headers & Receptacles



Connector System: **Wire-to-Board**

Number of Positions: **16**

Number of Rows: **2**

Centerline (Pitch): **2.5 mm [.098 in]**

PCB Mount Orientation: **Vertical**

Features

Product Type Features

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

Configuration Features

Connector Contact Load Condition	Fully Loaded
Number of Positions	16
Number of Rows	2
PCB Mount Orientation	Vertical

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------

Body Features

Primary Product Color	Natural
-----------------------	---------



Contact Features

PCB Contact Termination Area Plating Material Thickness	2 µm[78.74 µin]
Contact Layout	Matrix
Mating Pin Diameter	.6 mm[.024 in]
Contact Underplating Material Thickness	1.27 µm[50 µin]
Contact Mating Area Plating Material Thickness	2 µm[78.74 µin]
PCB Contact Termination Area Plating Material Finish	Bright
Contact Mating Area Plating Material Finish	Bright
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	4.2 A

Termination Features

Termination Post & Tail Diameter	.6 mm[.024 in]
Termination Post & Tail Length	3.4 mm[.134 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Alignment Type	Locating Boss
Mating Alignment Type	Polarization
Mating Retention	With
Panel Mount Feature	Without
PCB Mount Retention Type	Kinked Solder Tails
Mating Retention Type	Latch
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With

Housing Features

Housing Material	Nylon
Centerline (Pitch)	2.5 mm[.098 in]



Dimensions

	.901 in
Connector Height	9.8 mm[.386 in]
Connector Width	10.47 mm[.4 in]
Row-to-Row Spacing	2.5 mm[.098 in]

Usage Conditions

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Glow Wire Rating	Glow Wire
Compatible With Agency/Standards Products	UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	160
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability













Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 3-2324245-0 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 3-2324245-2 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 3-2324245-4 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 1-2323743-6 HOUSING, PLUG, GWT, 16P, DUAL ROW, EP2.5
 TE Part # 1-2323751-6 ASSY,HDR,VERT,GWT,NO-BOSS, DUAL ROW,EP2.5	 TE Part # 1-2324245-0 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 1-2324245-8 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 2-2324245-0 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5
 TE Part # 2-2324245-2 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 2-2324245-4 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 2-2324245-6 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 2-2324245-8 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5
 TE Part # 3-2324245-6 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 3-2324245-8 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	 TE Part # 4-2324245-0 ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5	


Also in the Series | Economy Power 2.5



Connector Contacts(6)



Connector Hardware(49)



PCB Headers & Receptacles(494)



Rectangular Power Connectors(43)




Wire-to-Board Connector Assemblies & Housings(305)

Customers Also Bought



TE Part #1-1625971-5
HSA25 1K2 5%



TE Part #2029181-3
3P VAL-U-LOK VRTHDR W/PGS GW




TE Part #1734795-1
RJ45,8P8C,SHD,W/O LED,DIP 6u"




TE Part #1-2232890-9
9P MONOPLUG 2.5 SELECTIVELY LOADED



TE Part #1-2825272-2
12P VERT HDR VAL-U-LOK HCS GW




TE Part #2-2324245-4
ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5



TE Part #2-2324245-6
ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5



TE Part #2-2360442-4
FOAMING PROOF UPPER TPA 2POS 24AWG



TE Part #4-2324245-0
ASSY,HDR,VERT,GWT,BOSSED,DUAL ROW, EP2.5



TE Part #5-368571-4
FOAMING PROOF PLUG 3POS YEL

Documents



Product Drawings

ASSY,HDR,VERT,GWT,BOSSSED,DUAL ROW, EP2.5

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2324245-6_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2324245-6_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2324245-6_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

7-1773461-6_EP2.5_Connector_Series

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English