




TE Internal #: 1-2825274-2
Header, Plug, Wire-to-Board, 18 Position, 4.2 mm [.165 in]
Centerline, Printed Circuit Board, UL 94V-0, Rectangular Power
Connectors
[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**
Connector & Housing Type: **Plug**
Connector System: **Wire-to-Board**
Number of Positions: **18**
Centerline (Pitch): **4.2 mm [.165 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	18
PCB Mount Orientation	Vertical
Number of Power Positions	0
Number of Signal Positions	12
Number of Rows	2

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

--	--



Multiple Contact Types	With
Contact Layout	Inline
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	13 A
Contact Retention Within Housing	With
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	2.03 μm[80 μin]

Termination Features

Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Mating Alignment Type	Keyed
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With
PCB Mount Retention Type	Boardlock
Mating Retention Type	Latch
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	4.2 mm[.165 in]
Housing Material	Polyamide

Dimensions

Connector Height	12.8 mm[.504 in]
PCB Thickness (Recommended)	1.78 mm[.7 in]
Product Width	9.75 mm[.384 in]
Product Length	26.4 mm[1.039 in]
Compatible Insulation Diameter Range	1.2 – 3.1 mm[.047 – .122 in]
Wire Size	.12 – 1.4 mm²
Row-to-Row Spacing	4.2 mm[.165 in]

Usage Conditions

--	--



Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power
---------------------	-------

Identification Marking

Circuit Identification Feature	With
--------------------------------	------

Industry Standards

CSA Rating	208567
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Method	Box & Tray, Tray
------------------	------------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits



as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

<p>TE Part # 2-2825274-4 24P VAL-U-LOK HCS VRTHDR W/PGS GW</p>	<p>TE Part # 2825274-2 2P VAL-U-LOK HCS VRTHDR W/PGS GW</p>	<p>TE Part # 1-2825260-2 12P VRT HDR VAL-U-LOK HCS V0</p>	<p>TE Part # 1-2825261-2 12P VAL-U-LOK HCS VRT HDR W/P V0</p>
<p>TE Part # 1-2825272-2 12P VERT HDR VAL-U-LOK HCS GW</p>	<p>TE Part # 1-2825274-0 10P VAL-U-LOK HCS VRTHDR W/PGS GW</p>	<p>TE Part # 2-2825274-0 20P VAL-U-LOK HCS VRTHDR W/PGS GW</p>	<p>TE Part # 2825274-4 4P VAL-U-LOK HCS VRTHDR W/PGS GW</p>
<p>TE Part # 2825274-6 6P VAL-U-LOK HCS VRTHDR W/PGS GW</p>	<p>TE Part # 2825274-8 8P VAL-U-LOK HCS VRTHDR W/PGS GW</p>		

Customers Also Bought

<p>TE Part #1-1623795-7 SQP10 7R5 5% WIRE</p>	<p>TE Part #1-794954-6 16P RCPT VAL-U-LOK V2</p>	<p>TE Part #1-794954-2 12P RCPT VAL-U-LOK V2</p>	<p>TE Part #794954-6 6P RCPT VAL-U-LOK V2</p>
---	--	--	---



TE Part #794954-4
4P RCPT VAL-U-LOK V2

TE Part #2825207-1
VAL-U-LOK SKT HCS SN 16AWG

TE Part #2825209-1
VAL-U-LOK SKT 16AWG HCS SN LP

TE Part #2-2176340-1
CRGCQ 0603 2K2 5%

TE Part #91388-2
PRO-CRIMPER DIE(ONLY)

TE Part #1-2825261-2
12P VAL-U-LOK HCS VRT HDR W/P V0

Documents

Product Drawings

12P VAL-U-LOK HCS VRTHDR W/PGS GW

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2825274-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2825274-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2825274-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

UL Report



English