

Product Drawings:

- [ATTENUATOR, FOPC BOA SC/UPC BP SM](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- [Singlemode Fixed Buildout Attenuators](#) (PDF, English)

Instruction Sheets:

- [Installation and Cleaning Procedure for Fiber Optic ...](#) (PDF, English)

CAD Files:

- None Available

[List all Documents](#)**Additional**

- [Prod](#)

Related P

- [Tool](#)

Product Features (Please use the Product Drawing for all design activity)**Product Type Features:**

- Product Type = Attenuator - Fiber Optic
- [Fiber Optic Attenuator Type](#) = Broadband Bandpass
- [Connector Type](#) = ST
- [Sealed](#) = No
- Comment = Designed to comply with Telcordia GR-910

Electrical Characteristics:

- [Attenuation \(dB\)](#) = 1.5
- Operating Wavelength (nm) = 1260 - 1360, 1430 - 1625
- Attenuation Value = Fixed

Termination Related Features:

- Mode = Singlemode

Body Related Features:

- [Attenuator Style](#) = B
- Reflectance $\leq$ (dB) =
- Fiber Packaging Style

Industry Standards:

- [RoHS/ELV Compliance](#) compliant
- [Lead Free Solder Process](#) lead free process
- RoHS/ELV Compliance RoHS compliant

Other:

- Brand = AMP

[Provide Website Feedback](#) | [Need Help?](#)[Home](#) | [Customer Support](#) | [Suppliers](#) | [Site Map](#) | [Privacy Policy](#) | [Browser Support](#)

© 2008 Tyco Electronics Corporation All Rights Reserved