



Dimensions

inches [mm]




Figure 1




Figure 2




Figure 3




Figure 4

Certifications & Ratings

- RoHS compliant
- NEMA 4X (Watertight only)
- IP66 (Watertight only)

Application

The 607 Series LED Panel Mount Indicators are designed for a variety of applications such as:

- Main power indication
- Remote power indication
- Status indication
- Maintenance and warning indication
- Instrumentation

... and many more!


Mechanical Information

Mounting Hole Size:	0.283" (7.2 mm)
Max Panel Thickness:	See part numbers
Mounting Torque:	0.362 lbs/ft (5 kg/cm) 0.217 lbs/ft or 3 kg/cm (Figure 5 only)

Specifications

Voltage Options:	2 VDC (resistor required) 6, 12 & 24 VDC (no resistor required)
Operating Temp:	-30 °C to +85 °C (-22 °F to +185 °F)
Storage Temp:	-40 °C to +85 °C (-40 °F to +185 °F)
Electrical Connection:	Solder terminals
Housing:	Protruding & recessed positions: Brass—Chrome Plated Internal position: Polycarbonate
Terminals:	Copper—Nickel Plated
Lock Washer:	Iron—Nickel Plated
Nut:	Brass—Nickel Plated

Figure 5



Ordering Information 607 Series

Standard		Watertight						
Part Number	Part Number	Color	Voltage (V DC)	Current (mA)	Intensity Typ. (mcd)	LED Positions	Figure	Panel Thickness
607-1112-110F	607-1112-310F	Red	2	15	22	Protruding	1	0.187" (4.75 mm)
607-1212-110F	607-1212-310F	Green			50			
607-1312-110F	607-1312-310F	Yellow			66			
607-1112-120F	607-1112-320F	Red	6		22		2	0.265" (6.75 mm)
607-1212-120F	607-1212-320F	Green			50			
607-1312-120F	607-1312-320F	Yellow			66			
607-1112-130F	607-1112-330F	Red	12		22			
607-1212-130F	607-1212-330F	Green			50			
607-1312-130F	607-1312-330F	Yellow			66			
607-2112-110F	607-2112-310F	Red	2		22	Recessed	3	0.136" (3.45 mm)
607-2212-110F	607-2212-310F	Green			50			
607-2312-110F	607-2312-310F	Yellow			66			
607-2112-120F	607-2112-320F	Red	6		22		4	0.336" (8.50 mm)
607-2212-120F	607-2212-320F	Green			50			
607-2312-120F	607-2312-320F	Yellow			66			
607-2112-130F	607-2112-330F	Red	12		22			
607-2212-130F	607-2212-330F	Green			50			
607-2312-130F	607-2312-330F	Yellow			66			
607-3132-120F	607-3132-320F	Red	6		20	Internal	5	0.187" (4.75 mm)
607-3232-120F	607-3232-320F	Green			45			
607-3332-120F	607-3332-320F	Yellow			60			
607-3132-130F	607-3132-330F	Red	12		20			
607-3232-130F	607-3232-330F	Green			45			
607-3332-130F	607-3332-330F	Yellow			60			
607-3132-140F	607-3132-340F	Red	24		20			
607-3232-140F	607-3232-340F	Green			45			
607-3332-140F	607-3332-340F	Yellow			60			

Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialightsignalsandcomponents.com
Warranty Statement: Except for the warranty expressly provided for [herein/above/below], Dialight disclaims any and all other warranties, express or implied, including, without limitation, any warranties of merchantability, fitness for a particular purpose, title, and noninfringement.

