

DTP04-4P-C015

✓ ACTIVE

DEUTSCH | DEUTSCH DT, DEUTSCH DTP


TE Internal #: DTP04-4P-C015

Housing for Male Terminals, Wire-to-Wire, 4 Position, 6.7 mm [.264 in] Centerline, Sealable, Gray, Wire & Cable, Power, Hybrid

[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DTP Housings



Connector System: **Wire-to-Wire**
Number of Positions: **4**
Connector & Housing Type: **Housing for Male Terminals**
Centerline (Pitch): **6.7 mm [.264 in]**
Sealable: **Yes**

[All DEUTSCH DTP Housings \(34\)](#)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing

Configuration Features

Blank Cavity Position	0
Connector Seal Code	E Seal
Number of Positions	4
Number of Rows	2

Electrical Characteristics



Operating Voltage	200 VAC
Nominal Voltage Architecture	200 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Gray

Contact Features

Contact Size	Size 12
Contact Type	Pin
Mating Pin Diameter	2.4 mm[.094 in]
Contact Current Rating (Max)	25 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA66 GF15
Centerline (Pitch)	6.7 mm[.264 in]

Dimensions

Connector Height	47.3 mm[1.86 in]
Product Width	26.9 mm[1.06 in]
Product Length	26.6 mm[1.05 in]
Row-to-Row Spacing	10.2 mm[.4 in]
Compatible Insulation Diameter Range	2.5 – 4 mm[.097 – .158 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Degree of Protection	IP68, IP6K9K
----------------------	--------------



Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Quantity	1
Packaging Method	Package

Other

Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.


Solder Process Capability	Not reviewed for solder process capability
---------------------------	--

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>




Compatible Parts

 TE Part # CAT-D48-SP729 DEUTSCH Sealing Plugs	 TE Part # CAT-D48-ST273 DEUTSCH Solid Contacts	 TE Part # WP-4P WEDGE LOCK, 4P, REC, ORG, DTP	 TE Part # CAT-D487-M8649 DEUTSCH DT Mounting Clips
 TE Part # 1011-118-0405 SEAL RET, 4P, GRY, DTP	 TE Part # 1924487-2 MOUNTING CLIP, AMPSEAL 16	 TE Part # CAT-D486-CH8172 DEUTSCH DTP Housings	 TE Part # DT-RT1 EXT TOOL, FRONT RELEASE
 TE Part # DTP4P-BT-EN BOOT, 4P, REC, ST, LONG, GRY	 TE Part # 1060-12-0144 PIN, SF, SIZE 12, 12-14, AU/SN	 TE Part # 1060-12-0166 PIN, SF, SIZE 12, 12-14, NI/SN	 TE Part # 1060-12-0222 PIN, SF, SIZE 12, 10, NI/NI
 TE Part # DTP4P-BT BOOT, 4P, REC, ST, GRY	 TE Part # 1060-12-0244 PIN, SF, SIZE 12, 10, AU/SN		

Also in the Series | **DEUTSCH DT**



Automotive Connector Caps & Covers (19)



Automotive Connector Locks & Position Assurance (87)



Automotive Housings (706)



Connector Backshells (61)



Connector Seals & Cavity Plugs (6)




Connector Strain Relief (28)



Insertion & Extraction Tools (3)




Other Automotive Connector Accessories (28)



PCB Headers & Receptacles (106)

Also in the Series | **DEUTSCH DTP**



Automotive Connector Locks & Position Assurance (4)




Automotive Housings (34)



Connector Backshells (1)




Insertion & Extraction Tools (3)



PCB Headers & Receptacles (5)



Customers Also Bought

 TE Part #208945-7 SZ 22 UNASSM KIT,CMC	 TE Part #DTP04-2P-C015 DEUTSCH DTP Housings	 TE Part #WP-4P WEDGE LOCK, 4P, REC, ORG, DTP	 TE Part #2-2112162-1 21POS,TAB2.8X0.8,TABHSG,CODE B, ASSY,SLD
 TE Part #1-1718485-5 AMP Carrier for Receptacle Inserts	 TE Part #DRB16-60SBE-L018 PLG, 60P, BLK, E, CAP, B	 TE Part #HDP24-24-23PN-L015 REC, 23P, BLK, N, THD, 16, P	 TE Part #HC5734 LEAD CONNECTOR 50mm +VE

Documents

Product Drawings

REC, 4P, GRY, E

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DTP04-4P-C015_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DTP04-4P-C015_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DTP04-4P-C015_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Engineering Report



English

[Engineering Report](#)

English

[Agency Approvals](#)

[UL Report](#)

English