# CONSMB001-SMD-G V ACTIVE

TE Internal #: CONSMB001-SMD-G

SMB RF Interface, Jack, 50 ohm, Snap-On, 12 GHz Operating

Frequency, 1 Position, Printed Circuit Board, Board Mount, -65 –

165 °C [-85 – 329 °F]

View on TE.com >



#### Connectors > RF Connectors > Coax Connectors





RF Interface: SMB

RF Connector Style: **Jack** 

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Snap-On

Operating Frequency: 12 GHz

## **Features**

## **Product Type Features**

Connector Product Type	Connector Assembly
RF Interface	SMB
RF Connector Style	Jack
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1

## **Electrical Characteristics**

Impedance $50 \Omega$
-----------------------

## **Body Features**

Cable Connector Orientation	Straight
Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Gold

### **Contact Features**

RF Connector Center Contact Plating Material	Gold	



RF Connector Center Contact Material	Brass
Termination Features	
Termination Method to PCB	Surface Mount
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Snap-On
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Usage Conditions	
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Circuit Application	Signal
Operating Frequency	12 GHz
Packaging Features	
Packaging Quantity	100
Packaging Method	Tray
Other	
Dielectric Material	PTFE

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability



#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

## Compatible Parts



TE Part # CONSMB012-G SMB Plug 50 Ohm Cable Crimp



TE Part # CSE-SBRM-152-SBRM SMB to SMB 152mm RG316













# Customers Also Bought





















## **Documents**

## **Product Drawings**

SMB Jack 50 Ohm PCB Surface Mount

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_CONSMB001-SMD-G\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_CONSMB001-SMD-G\_A.3d\_stp.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_CONSMB001-SMD-G\_A.3d\_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

SMB Jack PCB Surface-Mount Connector

English