

规格说明: Specifications:
电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN


物理性能: Mechanical:

1. 插拔力: Connector Mate and Umate Force
Mate force: 3.57kgf(MAX)
Umate force: 1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.2kgf(MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Ternmaplastics,
PBT White/Black
 2. 端子: Contact: Copper Alloy C2680
 3. 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀: Finish:
1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
 2. 外壳: Shell:
Nickel Plating

PCB LAYOUT



 深圳市万骏达电子有限公司 http://www.wanjunda.com		图号 (DWG NO)	单位 (UNIT): MM
品名 (ITEM NO)	AF 180 度 13.0 直角 卷边	版本 (REV)	A/0
料号 (PART NO)	USB2.0-AF-ZCI-JB-13.0	日期 (DATE)	2016.06.08
模号 (MODEL NO)		设计 (DESIGN)	
		审核 (CHECKED)	
		核准 (APPROVED)	
		比例 (SCALE) 1:1	

品名 (ITEM NO)	AF 180 度 13.0 直角 卷边	图号 (DWG NO)	单位 (UNIT): MM
料号 (PART NO)	USB2.0-AF-ZCI-JB-13.0	版本 (REV)	A/0
模号 (MODEL NO)		日期 (DATE)	2016.06.08
		设计 (DESIGN)	
		审核 (CHECKED)	
		核准 (APPROVED)	
		比例 (SCALE) 1:1	