

Part Number: 1511920016

Product Description : 2.00mm Pitch Milli-Grid Receptacle Housing, Dual Row, 16 Circuits,

Black, Glow-Wire Capable

Status: Active

Series Number: 151192

Product Category: Connector Housings

Documents & Resources

Drawings

Drawing 1511920016_sd.pdf

Packaging Design Drawing PK-151192-0001-001.pdf

3D Models and Design Files

3D Model 1511920016_stp.zip

Specifications

Application Specification 503940001-AS-000.pdf Application Specification 503940002-AS-000.pdf Product Specification PS-151192-0001-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | Connector Housings |
| Series | 151192 |
| Description | 2.00mm Pitch Milli-Grid Receptacle Housing, Dual Row, 16 Circuits, Black, Glow-Wire Capable |
| Application | Signal, Wire-to-Board |
| Product Family | Milli-Grid Connector System |
| Product Name | Milli-Grid |
| UPC | 889056795579 |

Agency

| CSA | LR19980 |
|-----|---------|
| UL | E29179 |

Physical

| Circuits (maximum) | 16 |
|--------------------------|------------|
| Circuits (maximum) | 10 |
| Color - Resin | Black |
| Flammability | 94V-0 |
| Gender | Receptacle |
| Glow-Wire Capable | Yes |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Resin | Polyester |
| Net Weight | 0.383/g |
| Number of Rows | 2 |
| Packaging Type | Bag |
| Panel Mount | No |
| Pitch - Mating Interface | 2.00mm |

| Pitch - Termination Interface | 2.00mm |
|-------------------------------|----------------|
| Polarized to Mating Part | Yes |
| Temperature Range - Operating | -55° to +105°C |

Solder Process Data

| Lead-Free Process Capability | N/A |
|------------------------------|-----|
|------------------------------|-----|

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|--|---------------|
| Milli-Grid Vertical, Dual Row, Through Hole Headers | <u>151117</u> |
| Milli-Grid Vertical, Dual Row, Surface Mount Headers | <u>151118</u> |
| Milli-Grid Right-Angle, Dual Row, Through Hole Headers | <u>151119</u> |
| Milli-Grid Right-Angle, Dual Row, Surface Mount Headers | <u>151120</u> |

Use with Part(s)

| Description | Part Number |
|---|--|
| Pre-Crimped Lead Milli-Grid Female-to-Milli-Grid Female, Gold (Au) Plating, 150.00mm Length, 24 AWG, Black | /content/molex/molex-dot- com/us/en/products/product-page- pdf.html/797581095.html |
| Pre-Crimped Lead Milli-Grid Female-to-Milli-Grid Female, Gold (Au) Plating, 300.00mm Length, 24 AWG, Black | /content/molex/molex-dot- com/us/en/products/product-page- pdf.html/797581096.html |
| Milli-Grid Female Crimp Terminals | 50394 |
| Milli-Grid Female Crimp Terminals | <u>87396</u> |