

# SPV 2,5/ 1-L BU - Plug

3041037

<https://www.phoenixcontact.com/us/products/3041037>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug, nom. voltage: 500 V, nominal current: 24 A, number of positions: 1, connection method: Spring-cage connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.08 mm<sup>2</sup>- 4 mm<sup>2</sup>, color: blue

## Product description

Connector element left, left housing without engagement pin, right opened without cover

## Your advantages

- Cable housing can be snapped on to the plugs, see figure below
- The plug with spring-cage connection is assembled directly on site by snapping together single-position plug elements
- The ST-COMBI plugs for self-assembly provide solutions that users can implement themselves
- Tested for railway applications

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3041037             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE02                |
| Product key                          | BE2144              |
| Catalog page                         | Page 320 (C-1-2019) |
| GTIN                                 | 4046356055000       |
| Weight per piece (including packing) | 3.321 g             |
| Weight per piece (excluding packing) | 3.17 g              |
| Customs tariff number                | 85366990            |
| Country of origin                    | PL                  |

# SPV 2,5/ 1-L BU - Plug

3041037

<https://www.phoenixcontact.com/us/products/3041037>



## Technical data

### Product properties

|                     |               |
|---------------------|---------------|
| Product type        | Terminal plug |
| Number of positions | 1             |
| Pitch               | 5.2 mm        |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 04 |
|------------------|----|

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                     |      |
|---------------------|------|
| Rated surge voltage | 6 kV |
|---------------------|------|

### Connection data

|                                                                   |                                                       |
|-------------------------------------------------------------------|-------------------------------------------------------|
| Nominal cross section                                             | 2.5 mm <sup>2</sup>                                   |
| Stripping length                                                  | 8 mm ... 10 mm                                        |
| Internal cylindrical gage                                         | A3                                                    |
| Connection in acc. with standard                                  | IEC 61984                                             |
| Conductor cross section rigid                                     | 0.08 mm <sup>2</sup> ... 4 mm <sup>2</sup>            |
| Cross section AWG                                                 | 28 ... 12 (converted acc. to IEC)                     |
| Conductor cross section flexible                                  | 0.08 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| Conductor cross section, flexible [AWG]                           | 28 ... 14 (converted acc. to IEC)                     |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>          |
| Nominal current                                                   | 24 A                                                  |
| Maximum load current                                              | 24 A (with 4 mm <sup>2</sup> conductor cross section) |
| Nominal voltage                                                   | 500 V                                                 |
| Nominal cross section                                             | 2.5 mm <sup>2</sup>                                   |

### Dimensions

|        |         |
|--------|---------|
| Width  | 5.2 mm  |
| Height | 23.4 mm |
| Depth  | 34 mm   |
| Length | 23.4 mm |
| Pitch  | 5.2 mm  |

### Material specifications

|                                        |                 |
|----------------------------------------|-----------------|
| Color                                  | blue (RAL 5015) |
| Flammability rating according to UL 94 | V0              |
| Insulating material group              | I               |
| Insulating material                    | PA              |

# SPV 2,5/ 1-L BU - Plug



3041037

<https://www.phoenixcontact.com/us/products/3041037>

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Static insulating material application in cold                          | -60 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C      |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg    |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed      |

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                                                          |
|------------------------------------------|--------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C (max. operating temperature see derating curve)                   |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                          |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                          |
| Permissible humidity (operation)         | 20 % ... 90 %                                                            |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                            |

## Standards and regulations


|                                  |           |
|----------------------------------|-----------|
| Connection in acc. with standard | IEC 61984 |
|----------------------------------|-----------|

## Mounting

|             |    |
|-------------|----|
| Thread type | () |
|-------------|----|

## Drawings

Diagram



Circuit diagram




# SPV 2,5/ 1-L BU - Plug

3041037

<https://www.phoenixcontact.com/us/products/3041037>



Schematic diagram



# SPV 2,5/ 1-L BU - Plug

3041037

<https://www.phoenixcontact.com/us/products/3041037>



## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3041037>



**IECEE CB Scheme**  
Approval ID: DE1-62736/B1/B2



**EAC**  
Approval ID: RU C-DE.BL08.B.00511

|                                                                                   |                                                        |                       |                       |                             |
|-----------------------------------------------------------------------------------|--------------------------------------------------------|-----------------------|-----------------------|-----------------------------|
|  | <b>VDE Zeichengenehmigung</b><br>Approval ID: 40019518 |                       |                       |                             |
|                                                                                   |                                                        | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG           |
|                                                                                   | Only flexible conductors                               | 500 V                 | -                     | -                           |
|                                                                                   | Only rigid conductors                                  | 500 V                 | -                     | -                           |
|                                                                                   |                                                        |                       |                       | Cross section $\text{mm}^2$ |
|                                                                                   |                                                        |                       |                       | 0.2 - 2.5                   |
|                                                                                   |                                                        |                       |                       | 0.2 - 4                     |



**cULus Recognized**  
Approval ID: E60425



**cULus Recognized**  
Approval ID: E60425

# SPV 2,5/ 1-L BU - Plug



3041037

<https://www.phoenixcontact.com/us/products/3041037>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141151 |
| ECLASS-12.0 | 27141151 |
| ECLASS-13.0 | 27250306 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002021 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# SPV 2,5/ 1-L BU - Plug

3041037  
<https://www.phoenixcontact.com/us/products/3041037>



## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)