






REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.05.26	阿树





主要技术参数、性能
The Main Thchnology Performance
额定电流、电压:50mA DC12V
Rate voltage,current:50mA DC12V
接触电阻:≤100mΩ
Contact resistance:≤100mΩ
按力:50gf
Operating force:50gf
行程:0.20± 0.1 0mm
Travel:0.20± 0.1 0mm
绝缘电阻:≥100MΩ
Insulated resistance:≥100MΩ
介电强度:≥250VAC/1min
Di electric strength:≥250VAC/1min

PAPT NO	TC-1101DE-X-X
Operating Force	B:160gf C:260gf
Height	code-x

code-x	H
A	4.3
B	4.8
C	5.0
D	5.3
E	5.5
F	6.0

⑤	Terminal	2	Brass (0.30t)	Plating silvering
④	Contact	1	F.ag/SUS	Natural
③	Base	1	PPA	
②	Cover	1	Spcc	Plating Nickel
①	Keystake	1	PPA	
ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING



电路图
CIRCUIT DIAGRAM

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树
CHECKED	
APPROVED	

VIEW:	
UNIT:	mm/in
SIZE:	A4

MODEL TYPE:	TACT SWITCH
PART NO.:	TC-1101DE-X-X
DWG NO.:	

SCALE	PAGE	REVISION
N/A	1/1	A1