



Figure similar

Selector switch, 16 mm, round, plastic, black, 2 switch positions O<I, momentary contact type, retraction from right, actuating angle 50 degree

|                                                    |                        |
|----------------------------------------------------|------------------------|
| product brand name                                 | SIRIUS                 |
| product designation                                | Selector switches      |
| design of the product                              | Single device round    |
| product type designation                           | 3SB2                   |
| <b>Enclosure</b>                                   |                        |
| number of command points                           | 1                      |
| <b>Actuator</b>                                    |                        |
| design of the actuating element                    | selector switch        |
| principle of operation of the actuating element    | momentary contact type |
| product extension optional light source            | No                     |
| color of the actuating element                     | black                  |
| material of the actuating element                  | plastic                |
| outer diameter of the actuating element            | 19 mm                  |
| type of unlocking device                           | without                |
| number of switching positions                      | 2                      |
| actuating angle                                    |                        |
| • clockwise                                        | 50°                    |
| <b>Front ring</b>                                  |                        |
| product component front ring                       | Yes                    |
| design of the front ring                           | Standard               |
| material of the front ring                         | plastic                |
| color of the front ring                            | black                  |
| <b>Holder</b>                                      |                        |
| material of the holder                             | Plastic                |
| <b>General technical data</b>                      |                        |
| product function                                   |                        |
| • EMERGENCY OFF function                           | No                     |
| • EMERGENCY STOP function                          | No                     |
| protection class IP                                | IP65                   |
| vibration resistance acc. to IEC 60068-2-6         | 20 ... 200 Hz: 5g      |
| operating frequency maximum                        | 1 000 1/h              |
| mechanical service life (switching cycles) typical | 300 000                |
| reference code acc. to IEC 81346-2                 | S                      |
| <b>Connections/ Terminals</b>                      |                        |
| tightening torque of the screws in the bracket     | 0.4 N·m                |
| <b>Ambient conditions</b>                          |                        |

- ambient temperature during operation
- ambient temperature during storage

-25 ... +70 °C  
-40 ... +80 °C

environmental category during operation acc. to IEC 60721

3K6

#### Installation/ mounting/ dimensions

|                                   |                      |
|-----------------------------------|----------------------|
| fastening method                  | front panel mounting |
| shape of the installation opening | round                |
| mounting diameter                 | 16 mm                |
| mounting height                   | 17 mm                |
| installation width                | 19 mm                |
| installation depth                | 50 mm                |

#### Certificates/ approvals

General Product Approval

Declaration of Conformity

Test Certificates



[Miscellaneous](#)



[Special Test Certificate](#)

Test Certificates

other

Railway

[Miscellaneous](#)

[Confirmation](#)

[Special Test Certificate](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SB2000-2BB01>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SB2000-2BB01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SB2000-2BB01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SB2000-2BB01&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SB2000-2BB01&lang=en)



last modified:

5/15/2020