

PML-P100 (D100)R - Prohibition sign



1014226

<https://www.phoenixcontact.com/us/products/1014226>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Prohibition sign, Roll, red/white, labeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, mounting type: adhesive, diameter: 100 mm, Number of individual labels: 250, text field height: 100 mm, text field width: 100 mm

Your advantages

- The color preprinted PML-P ... prohibition signs without symbols allow you to create custom prohibition notices
- The label consists of soft, highly flexible PVC film that molds itself to uneven surfaces
- The prohibition signs conform to the ISO 7010 international standard
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- Marking service: Phoenix Contact can custom-mark all PLM-P ... markers according to your specifications

Commercial data

Item number	1014226
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BG21
Product key	BG2611
Catalog page	Page 372 (C-3-2019)
GTIN	4046356784788
Weight per piece (including packing)	715 g
Weight per piece (excluding packing)	665.4 g
Customs tariff number	39199080
Country of origin	DE

PML-P100 (D100)R - Prohibition sign



1014226

<https://www.phoenixcontact.com/us/products/1014226>

Technical data

Product properties

Product type	Prohibition sign unprinted
Area of application	Prohibition signs
	Prohibition marking according to ISO 7010
Type	circular

Data management status

Article revision	02
------------------	----

Marking

Number of individual labels	250
Number of individual labels per row	1

Dimensions

Width	100 mm
Text field width	100.00 mm
Height	100 mm
Text field height	100.00 mm
Diameter	100.00 mm

Material specifications

Color	red/white
Material	PVC
Components	Silicone-free

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 90 °C
Ambient temperature (assembly)	> 10 °C
Recommended ambient temperature (storage/transport)	22 °C
Recommended humidity (storage/transport)	50 % ... 55 % (Storage in a dry and dark place in the original packaging is recommended)
Shelf life	2 years

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	adhesive
---------------	----------

PML-P100 (D100)R - Prohibition sign



1014226

<https://www.phoenixcontact.com/us/products/1014226>

Classifications

ECLASS

ECLASS-11.0	40200202
ECLASS-13.0	40200202
ECLASS-12.0	40200202

ETIM

ETIM 9.0	EC001777
----------	----------

UNSPSC

UNSPSC 21.0	55121700
-------------	----------

PML-P100 (D100)R - Prohibition sign



1014226
<https://www.phoenixcontact.com/us/products/1014226>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com