## Molded Parts Specification Control Drawing


1. All dimensions are in  $\frac{\text{inches}}{[\text{millimeters}]}$ 


2. Dimensions appearing in table are as follows:

a - As Supplied

b - After Unrestricted Recovery

- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
- Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.
- 5. On sizes 228A011 & 021 the .18 dia molding port will be eliminated. The .12 dia molding port on top of part will be enlarged to .18 dia.





228A011 thru 097

TABLE OF DIMENSIONS														
PART	н		J		P R		s	JO	Т	U	HW	JW	c.	
NÜMBER	Min	Max	Min	Max	±10%	±10%	±10%	±10%	±10%	±10%	±20%	±20%	±10°	±5*
	a	b	a	b	b	b	b	ь	b	b	b	ь	b	ь
228A011	.42 [10,7]	<u>.31</u> [7,9]	.18 [4,6]	.08 [2,0]	.80 [20,3]	.80 [20,3]	<u>.63</u> [16,0]	. <u>20</u> [5,1]	N/A	. <u>50</u> [12,7]	.05 [1,3]	.04 [1,0]	135*	90.
228A021	.54 [13,7]	.41 [10,4]	.26 [6,6]	<u>.12</u> [3,0]	1.00 [25,4]	.91 [23,1]	.66 [16,8]	. <u>30</u> [7,6]	N/A	. <u>64</u> [16,3]	.06 [1,5]	.04 [1,0]	135*	90.
228A032	.76 [19,3]	.56 [14,2]	.32 [8,2]	.16 [4,1]	1.16 [29,5]	1.01 [25,7]	.76 [19,3]	. <u>32</u> [8,1]	. <u>58</u> [14,7]	. <u>65</u> [16,5]	.09 [2,3]	.07 [1,8]	135°	90.
228A042	.94 [23,9]	.70 [17,8]	.46 [11,7]	. <u>22</u> [5,6]	1.56 [39,6]	1.30 [33,0]	.86 [21,8]	. <u>37</u> [9,4]	<u>.66</u> [16,8]	<u>.81</u> [20,6]	<u>.11</u> [2,8]	<u>.04</u> [1,0]	135*	90.
228A053	1.18 [30,0]	<u>.88</u> [22,4]	<u>.58</u> [14,7]	<u>.28</u> [7,1]	1.89 [48,0]	1.52 [38,6]	<u>.97</u> [24,6]	. <u>49</u> [12,4]	<u>.70</u> [17,8]	1 <u>.12</u> [28,4]	.14 [3.6]	.05 [1,3]	135*	90.
228A064	1.49 [37,8]	1.11 [28,2]	.75 [19,1]	.36 [9,1]	2.33 [59,2]	1.93 [49,0]	1.24 [31,5]	.65 [16,5]	. <u>90</u> [22,9]	1 <u>.30</u> [33,0]	<u>.18</u> [4,6]	.07 [1,8]	135*	90.
228A075	1.85 [47,0]	1.38 [35,1]	1.40 [35,6]	<u>.64</u> [16,3]	3.20 [81,3]	2.17 [55,1]	1.41 [35,8]	1 <u>.20</u> [30,5]	1 <u>.00</u> [25,4]	2 <u>.30</u> [58,4]	.18 [4,6]	.12 [3,0]	135*	90.
228A086	2.34 [59.4]	1.75 [44,5]	1.72 [43.7]	.82 [20,8]	4.06 [103,1]	2.88 [73,2]	1.78 [45,2]	1 <u>.57</u> [39,9]	1 <u>.25</u> [31,8]	2.86 [72,6]	.28 [7,1]	.19 [4,8]	135°	90.
228A097	3.20 [81,3]	2.25 [57,2]	2.19 [55,6]	1.05 [26,7]	5.26 [133,6]	3.50 [88,9]	2.09 [53,1]	1 <u>.90</u> [48,3]	1 <u>.40</u> [35,6]	3 <u>.40</u> [86,4]	<u>.37</u> [9,4]	.22 [5,6]	135°	90.

**TUCO**/Electronics/Raychem

TYCO ELECTRONICS 307 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision: K

Date: 3/26/02

Part Number :

Part Number :

Part Number :

228A011 thru 097

228A011 thru 097


Description: Boot, 90°, Thick Wall

Description: Boot, 90°, Thick Wall

## Molded Parts Specification Control Drawing

0.	COATING DESCRIPTION
8	Adhesive
8	Adhesive

COMPATABILITY CHART									
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION				
-3	Polyolefin, Semi-rigid	RT-301	/42, /86	S-1017, S-1048	Adhesive				
-4	Polyolefin, Flexible	RT-1304	/42, /86	S-1017, S-1048	Adhesive				
-5	Neoprene	RT-501	N/A						
-6	Silicone	RT-602	N/A						
-25	Elastomer, Fluid Resistant	RT-1325	/42, /86	S-1017, S-1048	Adhesive				



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

## **TUCO**/Electronics/Raychem

TYCO ELECTRONICS 307 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025

Revision: K Date: 3/26/02 Part Number :

228A011 thru 097 Description: Boot, 90°, Thick Wall

CAD FILE MP02041