


# QTC 2,5-QUATTRO-PE - Ground terminal



3206448

<https://www.phoenixcontact.com/us/products/3206448>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ground terminal, number of connections: 4, connection method: Quick connection, cross section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/7,5, color: green-yellow

## Your advantages

- Same shape and pitch as the feed-through terminal blocks
- Contact is made free from mechanical and electrical errors by simply snapping onto the DIN rail
- All the requirements of standard IEC 60947-7-2 are met

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3206448             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE03                |
| Product key                          | BE3123              |
| Catalog page                         | Page 263 (C-1-2019) |
| GTIN                                 | 4046356898522       |
| Weight per piece (including packing) | 21.073 g            |
| Weight per piece (excluding packing) | 19.7 g              |
| Customs tariff number                | 85369010            |
| Country of origin                    | CN                  |

# QTC 2,5-QUATTRO-PE - Ground terminal



3206448

<https://www.phoenixcontact.com/us/products/3206448>

## Technical data

### Product properties

|                       |                       |
|-----------------------|-----------------------|
| Product type          | Ground terminal block |
| Number of connections | 4                     |
| Number of rows        | 1                     |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 01 |
|------------------|----|

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                                      |                     |
|------------------------------------------------------|---------------------|
| Grounding foot                                       | Yes                 |
| Number of connections per level                      | 4                   |
| Frequency of connections with the same cross section | 100                 |
| Nominal cross section                                | 2.5 mm <sup>2</sup> |
| Rated cross section AWG                              | 14                  |

### Level 1 above 1+2 below 1+2

|                                         |                                                                |
|-----------------------------------------|----------------------------------------------------------------|
| Note                                    | Please observe the current carrying capacity of the DIN rails. |
| Material wire insulation                | PVC / PE                                                       |
| Connection in acc. with standard        | IEC 60947-7-2                                                  |
| Conductor cross section rigid           | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                    |
| Cross section AWG                       | 20 ... 14 (converted acc. to IEC)                              |
| Conductor cross section flexible        | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>                    |
| Conductor cross section, flexible [AWG] | 20 ... 14 (converted acc. to IEC)                              |

### Dimensions

|                    |          |
|--------------------|----------|
| Width              | 6.2 mm   |
| End cover width    | 2.2 mm   |
| Height             | 102.4 mm |
| Depth              | 37.8 mm  |
| Depth on NS 35/7,5 | 39.3 mm  |
| Depth on NS 35/15  | 46.8 mm  |

### Material specifications

|                                        |              |
|----------------------------------------|--------------|
| Color                                  | green-yellow |
| Flammability rating according to UL 94 | V0           |

# QTC 2,5-QUATTRO-PE - Ground terminal



3206448

<https://www.phoenixcontact.com/us/products/3206448>

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Insulating material group                                               | I           |
| Insulating material                                                     | PA          |
| Static insulating material application in cold                          | -60 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C      |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg    |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed      |

## Cable/line

|                                |        |
|--------------------------------|--------|
| Wire diameter incl. insulation | 3.8 mm |
|--------------------------------|--------|

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Environmental and real-life conditions

### Oscillation/broadband noise

|                        |                                                |
|------------------------|------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2008-03            |
| Spectrum               | Service life test category 2, bogie-mounted    |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | $6.12 \text{ (m/s}^2\text{)}^2\text{/Hz}$      |
| Acceleration           | 3.12g                                          |
| Test duration per axis | 5 h                                            |
| Test directions        | X-, Y- and Z-axis                              |
| Result                 | Test passed                                    |

### Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2008-03 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 30g                                 |
| Shock duration                 | 18 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

### Ambient conditions

|                                 |                                                                                                                              |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation) | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------|

# QTC 2,5-QUATTRO-PE - Ground terminal



3206448

<https://www.phoenixcontact.com/us/products/3206448>

|                                          |                                                                           |
|------------------------------------------|---------------------------------------------------------------------------|
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                           |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                           |
| Permissible humidity (operation)         | 20 % ... 90 %                                                             |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                             |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-2 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/7,5 |

# QTC 2,5-QUATTRO-PE - Ground terminal


3206448

<https://www.phoenixcontact.com/us/products/3206448>



## Drawings

Circuit diagram



# QTC 2,5-QUATTRO-PE - Ground terminal

3206448

<https://www.phoenixcontact.com/us/products/3206448>



## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3206448>



**EAC**  
Approval ID: RU C-DE.BL08.B.00539

| <div><b>cULus Recognized</b><br/>Approval ID: E60425</div> |                       |                       |                   |                             |
|---------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                                                                                                                                 |                       |                       |                   |                             |
|                                                                                                                                             | -                     | -                     | 20 - 14           | -                           |
| Use group C                                                                                                                                 |                       |                       |                   |                             |
|                                                                                                                                             | -                     | -                     | 20 - 14           | -                           |

# QTC 2,5-QUATTRO-PE - Ground terminal



3206448

<https://www.phoenixcontact.com/us/products/3206448>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141141 |
| ECLASS-13.0 | 27250103 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000901 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# QTC 2,5-QUATTRO-PE - Ground terminal



3206448

<https://www.phoenixcontact.com/us/products/3206448>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)