




Relays & Contactors > Relays > Power Relays



Relay Type: **General Purpose Power Relay**  
Coil Magnetic System: **Monostable**  
Coil Power Rating DC: **.245 W**  
Coil Resistance: **9391  $\Omega$**   
Coil Special Features: **UL Coil Insulation Class F**

Features

Product Type Features

|            |                             |
|------------|-----------------------------|
| Relay Type | General Purpose Power Relay |
|------------|-----------------------------|

Configuration Features

|                         |                            |
|-------------------------|----------------------------|
| Coil Special Features   | UL Coil Insulation Class F |
| Contact Arrangement     | 1 Form C SPDT-CO           |
| Contact Number of Poles | 1                          |

Electrical Characteristics

|                                                       |               |
|-------------------------------------------------------|---------------|
| Insulation Initial Dielectric Between Open Contacts   | 1000 Vrms     |
| Contact Limiting Making Current                       | 8 A           |
| Contact Limiting Short-Time Current                   | 8 A           |
| Contact Limiting Continuous Current                   | 8 A           |
| Insulation Initial Dielectric Between Contacts & Coil | 5000 Vrms     |
| Contact Limiting Breaking Current                     | 8 A           |
| Coil Power Rating DC                                  | .245 W        |
| Coil Resistance                                       | 9391 $\Omega$ |
|                                                       |               |



|                                 |            |
|---------------------------------|------------|
| Coil Voltage Rating             | 48 VDC     |
| Contact Current Rating          | 8 A        |
| Contact Switching Load (Min)    | 10mA @ 12V |
| Contact Switching Voltage (Max) | 400 VAC    |
| Contact Voltage Rating          | 250 VAC    |

Body Features

|                |              |
|----------------|--------------|
| Product Weight | 8 g[.282 oz] |
|----------------|--------------|

Contact Features

|                  |          |
|------------------|----------|
| Contact Material | AgNi0.15 |
|------------------|----------|

Termination Features

|                        |                 |
|------------------------|-----------------|
| Relay Connection Type  | PCB Termination |
| Terminal Configuration | Solder Pins     |

Mechanical Attachment

|                    |                       |
|--------------------|-----------------------|
| Product Mount Type | Printed Circuit Board |
|--------------------|-----------------------|

Dimensions

|                                             |                  |
|---------------------------------------------|------------------|
| Insulation Clearance Between Contact & Coil | 8 mm[.315 in]    |
| Insulation Creepage Between Contact & Coil  | 8 mm[.315 in]    |
| Product Width                               | 10.1 mm[.397 in] |
| Product Length                              | 28.5 mm[1.12 in] |
| Product Height                              | 12.3 mm[.484 in] |

Usage Conditions

|                                         |               |
|-----------------------------------------|---------------|
| Environmental Category of Protection    | RTIII         |
| Environmental Ambient Temperature (Max) | 70 °C[158 °F] |

Operation/Application

|                      |             |
|----------------------|-------------|
| Current Type         | DC          |
| Solder Process       | Wave Solder |
| Coil Magnetic System | Monostable  |

Packaging Features

|                  |                  |
|------------------|------------------|
| Packaging Method | Box & Tube, Tube |
|------------------|------------------|

Other

|                           |            |
|---------------------------|------------|
| Length Class (Mechanical) | 25 – 30 mm |
|---------------------------|------------|



|                                         |            |
|-----------------------------------------|------------|
| Environmental Ambient Temperature Class | 50 – 70 °C |
| Height Class (Mechanical)               | 12 – 13 mm |
| Coil Power Rating Class                 | .2 – .3 W  |
| Width Class (Mechanical)                | 10 – 12 mm |
| Contact Current Class                   | 16 A       |

Product Compliance


For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.                                                                                  |
| Solder Process Capability                     | Wave solder capable to 260°C                                                                                                    |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 7-1393161-3  
RY78600



Also in the Series |

SCHRACK Miniature Power PCB RYII



Power Relays(101)

Customers Also Bought



TE Part #HDP24-24-31PE  
DEUTSCH HDP20 Housings



TE Part #2112301-1  
PROTECTION CAP, FOR REC.HSG GROUP C




TE Part #5767007-8  
MICT,260PLUG,38,ASSY,.025,REC



TE Part #1-1991253-5  
15 WAY LOW COST D SUB BACKSHEL



TE Part #1419108-1  
RT114012



TE Part #2032439-1  
RF CA,UMCC1 TO SMA PLUG,1.37 MM,L200MM



TE Part #180984  
FASTON 250 BOOT FLAG NYLON NAT



TE Part #CM9614-000  
SBP100143WE5

Documents

CAD Files

Customer View Model

ENG\_CVM\_CVM\_2-1393225-2\_D.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-1393225-2\_D.3d\_stp.zip

English

Customer View Model

ENG\_CVM\_CVM\_2-1393225-2\_D.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



Miniature Power PCB Relay RYII

English

Product Specifications

Definitions General Purpose Relays

English

Agency Approvals

VDE Certificate

English