

A

B

C

D

E

F

G

A

B

C

D

E

F

G

MAPX

MODIFICATION

DATE

NOTES:

1. HOUSING: SEE NOTES,
TERMINAL: SEE NOTES,
SHELL: SEE NOTES.

SPECIFICATION:

1. ELECTRICAL CHARACTERISTIC:

CONTACT RESISTANCE: $30M\Omega$ MAX
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN
INSULATION RESISTANCE: $1000M\Omega$ MIN

2. MECHANICAL CHARACTERISTIC:



INSERTION FORCE: 35N(3.57KGF) MAX
EXTRACTION FORCE: $10\sim35N$ (1.02~3.57KGF) MIN
DURABILITY: 1500 CYCLES EXTRACTION FORCE: $10\sim35N$
3000 CYCLES MIN
5000 CYCLES EXTRACTION FORCE: $3\sim35N$

3. ENVIRONMENTAL:


OPERATING TEMPERATURE: $-55^{\circ}C+85^{\circ}C$

4. Contact finish:





- 01:Selective Gold Flash
02:Selective Gold 3U"
03:Selective Gold 5U"
04:Selective Gold 15U"
05:Selective Gold 30U"



FRONT EDGE OF CONNECTOR
PCB LAYOUT



SECTION A-A



产品图

PRODUCT CHART DWG

公差一览表

TOLERANCE UNLESS OTHERWISE

X.	±0.25	X.	±5.°
.X	±0.20	.X	±2.°
.XX	±0.15	.XX	±1.°
.XXX	±0.10	.XXX	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	Z-Y-B	制图料号 PRODUCT PART NO.	910-461A1017Y10100
比例 SCALE	1:1	审核 CHKD		产品名称 PRODUCT NO.	AF10.0C款180度无脚无边铁壳 PBT白胶6.5无耳朵
日期 DATE	2012.06.15	核准 APPD		角法 VIEW	版本 VER
					A0