

SIGN	DATE	DESCRIPTION	APPROVER
△	2010.03.31	Add the 2p mark	Jacke
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material:

- Item a :Terminal housing:Thermoplastic (UL94 V-0)
- Item b :With flange screw: Steel Zinc plated, M2.5"/+/-"

Electrical (Match with A0 series)

- Voltage rating: 300V
- Current rating: 10A
- Wire range: 0.5-1.0mm²/1.5-2.5mm²
- Withstanding Voltage: 1.6KV

KI xx 50 x 3 xxxx G

No. OF POLES
02 2 CONTACTS
03 3 CONTACTS
...
24 24 CONTACTS

Color
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)

G: Pb<40000ppm
0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

N = Number of poles
Dim A=Nx5.08
Dim B=(N-1)x5.08

Dim. Poles	Dim A	Dim B
2-6p	±0.20	±0.20
7-12p	±0.25	±0.25
13-16p	±0.30	±0.30
17-24p	±0.40	±0.35

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE	KI 5.08 SERIES (加高有耳)						
PART NO.	KIxx50x3xxxxG			DWG NO.	8KI0104		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Jacke 2010.03.31	Jacke 2010.03.31			UNIT: mm	X. ±0.50
						SCALE: 2/1	X.X ±0.30
				SHEET: 01/01		REV.: C	X.XX ±0.10
							X° ±1°

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

<u>KI0250530000G</u>	<u>KI0350530000G</u>	<u>KI0450530000G</u>	<u>KI0550530000G</u>	<u>KI0650530000G</u>	<u>KI0750530000G</u>
<u>KI0850530000G</u>	<u>KI0950530000G</u>	<u>KI1050530000G</u>	<u>KI1150530000G</u>	<u>KI1250530000G</u>	<u>KI1350530000G</u>
<u>KI1450530000G</u>	<u>KI1550530000G</u>	<u>KI1650530000G</u>	<u>KI1750530000G</u>	<u>KI1850530000G</u>	<u>KI1950530000G</u>
<u>KI2050530000G</u>	<u>KI2150530000G</u>	<u>KI2250530000G</u>	<u>KI2350530000G</u>	<u>KI2450530000G</u>	