



Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Tab**

Wire Size: **2.1 – 3.31 mm²**

Mating Tab Width: **4.75 mm [.187 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	4.75 mm[.187 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Pre-Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Dimple

Dimensions

Terminal Material Thickness	.41 mm[.016 in]
Product Length	26.7 mm[1.05 in]
Compatible Insulation Diameter Range	3.1 – 4.1 mm[.12 – .16 in]
Wire Size	2.1 – 3.31 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	2500
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 160786-2 FF 250 TAB 0.5-1.5MM2 TPPB	 TE Part # 180352-2 FF 250 TAB 4-6MM2 PTBR	 TE Part # 170151-2 FF 250 TAB 18-14AWG PTBR	 TE Part # 160887-4 FF 110 TAB 0.5-1.0MM2 PTPPB
 TE Part # 160762-4 FF 110 TAB 0.5-1.5MM2 PTPBR	 TE Part # 175042-1 FF 187 REC 2-3MM2 PTBR	 TE Part # 160923-2 FF 110 TAB 24-20 AWG .016 PTPB	 TE Part # 60434-1 FF 187 TAB 20-16AWG TPBR
 TE Part # 170030-5 FF 250 TAB 20-14AWG PTBR	 TE Part # 144839-2 FF 5MM TAB 17-12 AWG .031 PTPB	 TE Part # 175040-1 FF 187 REC 0.5-1.25MM2 PTBR	

Also in the Series | FASTIN-FASTON 187

 Crimp Terminal Housings(6)	 Insertion & Extraction Tools(1)	 Quick Disconnects(20)
--------------------------------	-------------------------------------	---------------------------

Customers Also Bought






TE Part #1473672-2
TH/.025 CONNECTOR SYSTEM,
HOUSING




TE Part #175094-1
O4O HYBRID I/O REC CONT 24-20



TE Part #284223-3
24 POS.KIT ASSY FOR AIR BAG (G



TE Part #1612120-1
11DIA SQUIB SLIM MK-2 PLUG HSG



TE Part #175042-1
FF 187 REC 2-3MM2 PTBR



TE Part #1612123-1
SQUIB FERRITE



TE Part #2109234-2
MOS 6P RETAINER HSG

Documents

Product Drawings

FF 187 TAB 2-3MM2 PTBR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_175048-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_175048-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_175048-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

APPLICATION SPECIFICATION CRIMPING .187 SERIES TAB AND RECEPTCLE CONTACTS

Japanese

Application Specification

Japanese

APPLICATION SPECIFICATION CRIMPING .187 SERIES TAB AND RECEPTCLE CONTACTS

English

175048-1

Tab, 14 – 12 AWG Wire Size, 2.1 – 3.31 mm² Wire Size, Mating Tab Width 4.75 mm [.187 in], Straight, Brass, FASTIN-FASTON 187, Quick Disconnects

