

Cable connector - HC-26PDN8A80FA - 1623291

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Cable connector, straight, Screw locking, M27, number of positions: 26, type of contact: Pin, Crimp connection, shielded: yes, cable diameter range: 2 mm ... 14.5 mm, with special knurl



Key Commercial Data

Packing unit	12 pc
GTIN	4 055626 273198
GTIN	4055626273198

Technical data

General

Note	Order information: Order crimp contacts Ø 1 mm separately
Type of locking	Screw locking
Direction of rotation of contact chamber numbering	Standard
Coding	N
Contact connection method	Crimp connection
Type of contacts	Pin
Number of positions	26
Contact diameter of power contacts	1 mm
Nominal current per power contact at 25°C	8 A
Conductor entry	2 mm 14.5 mm
Pg housing screw connection	none

Ambient conditions

Degree of protection	IP67, when plugged in

Specifications according to DIN EN 61984:2001

Nominal / operating voltage of power contacts	150 V
Rated surge voltage of power contacts	1.5 kV
Overvoltage category of power contacts	II



Cable connector - HC-26PDN8A80FA - 1623291

Technical data

Specifications according to DIN EN 61984:2001


Degree of pollution of power contacts	3

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1623291