

Item no.:	284-624
Product description:	DISTRIBUTION TERMINAL BLOCK; 3 x CAGE CLAMP [®] connection 10 mm ² ; 1 x SCREW-CLAMP CONNECTION 35 MM ² /AWG 2; LATERAL MARKING; for DIN 35 rail; FRONT-/SIDE-ENTRY



Packing unit 15 pieces

Product group	1 (Rail Mounted Terminal Blocks)
Cross section from [mm ²]	0,2 mm ²
Cross section to [mm ²]	10 mm ²
Cross section from [AWG]	24 AWG
Cross section to [AWG]	8 AWG
Connection method	CAGE CLAMP [®] CONNECTION
Number of strands	73
Cross section from [mm ²]	6 mm ²
Cross section to [mm ²]	35 mm ²
Cross section from [AWG]	10 AWG
Cross section to [AWG]	2 AWG
Measured voltage EN	800 V
Measured shock voltage	8 kV
Pollution degree	3
Current intensity EN	125 A
Weight	55,6 g
Color	blue
Wiring type	Front-/Side-entry
No. of connection Points	4
No. of potentials	1
Height	39,5 mm
Height	1,55 in



Width	0,689 in
Depth	89 mm
Depth	3,507 in
Strip length from	12 mm
Strip length to	14 mm
Strip length	0,51 in



Item number	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
284-624	ABS	05-HG476175/1-PDA	500	125	35
284-624	BV	07436/C0			0,2-10
284-624	CB-certificateChina	NL10208	800	125	35
284-624	CCA	NL5910	800		35
284-624	CSA	154112-1536073	600	110	1x10-2/3x24-8
284-624	DNV	E7570	500	125	35
284-624	GL	17295-00HH	500	125	35
284-624	KEMA	2082859.11	800	125	35
284-624	LR	91/20112(E5)	500	125	35
284-624	PRS	TE/1718/880590/08	800		35
284-624	RMR	11130002	500	125	35
284-624	UL	E45172	600	115	24-8
284-624	UR	E45172	600	115	24-8

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected