

E	1	2	3	4	5	6		7		8	
	SAMZO REAC/ROHS					REV	ECN NO	DESCRIPTION	DESIGN	APPROVAL	DATE
						A1	NEW	Replace frame			2013.02.12
D	技术要求: Technical requirements: 1.打铜底0.5-1UM,镍底2-2.5UM,哑锡3-5UM。 Copper base 0.5 - 1 UM, nickel base 2 - 2.5 UM, matte tin 3 - 5 UM. 2.不得有脚变形, 毛刺等缺陷。 There shall be no defects such as pin deformation and burrs. 3.插脚尖部符合可焊性要求。 The tip of the insertion pin shall meet the solderability requirements. 4.螺纹需符合通止规要求。 The thread shall meet the requirements of the go and no-go gauge. 5.材质: 黄铜H65。 Material: Brass H65. 6.过载电流: 50A Overload current: 50A 7.牙孔规格 M4 The specification of the threaded hole M4 8.未标注尺寸公差值按GB/T1184-1996H级 Unmarked dimensional tolerance values are in accordance with Grade H of GB/T1184-1996 9.螺丝扭力: 2.0Nm Screw torque: 2.0Nm 10.盐雾试验: 48小时 Salt spray test: 48H										
C											
B											
A											

911 85 40 C D4

Pressing hole specification: M4
 Mold number: CS034
 Pin height: 4.0mm
 Height above the board: 8.5mm
 Specification size: 9.7*11.1mm

PCB LAYOUT

ITEM	DESCRIPTION	MATERIAL	QTY	FINISH/COLOR							
A	Subject	H62(Y2)	1	tin plating							
B	Gasket	SPCC	1	tin plating							
								GENERAL TOLERANCE			
								≥0~2<	±0.15		
					DESIGN	WANGGUIFA	2018.06.12	≥2~5<	±0.25		
					CHECKED	ZHENGUILAN	2018.06.12	≥0~2<	±0.15		
F					APPROVED	LILIANJIANG	2018.06.14	≥5	±0.35		

FIRST VIEW

SCALE 1:1 UNIT mm

The copyright belongs to samzo parts [China] Co., Ltd. please use the material after samzo parts agree to authorize. The final right of interpretation belongs to samzo parts. WWW.KKK-JP.COM

TITLE: 9.7*11.1*14mm

DWG NO: 911C-P014

PART NO: 911C-130940

MODEL NO: 9118540CD4

NAME: PCB soldering terminal

SAMZO COMPONENTS

Electronic switch and connector manufacturer