


DIMENSIONS: Inch [mm]
CO-PLANARITY: 0.004 [0.10]

TOLERANCES: ±0.005 INCH IF NOT SPECIFIED



PART NO.: TG24-S001NCRL

T1/E1/CEPT/ISDN-PRI TRANSFORMER MODULE RoHS COMPLIANT

COMPATIBLE TO LEAD-FREE SOLDERING PROCESS CONDITION PER IPC/JEDEC J-STD-020C UL/EN60950 AND DEMKO RECOGNIZED EXTENDED OPERATING TEMPERATURE -40/+85°C

ELECTRICAL SPECIFICATIONS @25° C

TURNS RATIO P12-10:P1-3 1CT:1.36CT±2% P4-6:P9-7 1CT:1.36CT±2% OCL P4-6,P12-10 1.5mH typ DCR P4-6,P12-10 0.9Ω max Cw/w 40pF max LL P4-6,P12-10 $0.5\mu H max$ CROSSTALK 0.5-5MHz -60dB typ 1,500Vrms **ISOLATION**



HALO/PBL

CALIFORNIA, USA KOWLOON, HONG KONG SINGAPORE

	TITLE	ISOLATION TRANSFORMERS			SIGNATURES		DATE	REV.	DESC.	DATE
	FOR	FOR T1/E1 (1:1.36,1:1.36)			DRAWN	PETER LU	2/13/08	Α	FIRST ISSUE	2/13/08
					CHECKED	LEI KEONG	2/13/08			
┪	PART NO.				APPROVED	PETER LU	2/13/08			
	SCALE	NONE	PAGE	1 of 1	FILE	1505NCRL.DWG				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HALO Electronics:

TG24-S001NCRL TG24-S001NCRLTR