



Power contactor, AC-3 7 A, 3 kW / 400 V 1 NO, 200 V AC, 50 Hz 200-220 V, 60 Hz, 3-pole, Size S00, screw terminal

|                                                                                                  |                            |
|--------------------------------------------------------------------------------------------------|----------------------------|
| product brand name                                                                               | SIRIUS                     |
| product designation                                                                              | Power contactor            |
| product type designation                                                                         | 3RT2                       |
| <b>General technical data</b>                                                                    |                            |
| size of contactor                                                                                | S00                        |
| product extension                                                                                |                            |
| • function module for communication                                                              | No                         |
| • auxiliary switch                                                                               | Yes                        |
| power loss [W] for rated value of the current at AC in hot operating state                       | 1.2 W                      |
| • per pole                                                                                       | 0.4 W                      |
| power loss [W] for rated value of the current without load current share typical                 | 4.8 W                      |
| surge voltage resistance                                                                         |                            |
| • of main circuit rated value                                                                    | 6 kV                       |
| • of auxiliary circuit rated value                                                               | 6 kV                       |
| maximum permissible voltage for safe isolation between coil and main contacts acc. to EN 60947-1 | 400 V                      |
| shock resistance at rectangular impulse                                                          |                            |
| • at AC                                                                                          | 6,7g / 5 ms, 4,2g / 10 ms  |
| shock resistance with sine pulse                                                                 |                            |
| • at AC                                                                                          | 10,5g / 5 ms, 6,6g / 10 ms |
| mechanical service life (switching cycles)                                                       |                            |
| • of contactor typical                                                                           | 30 000 000                 |
| • of the contactor with added electronically optimized auxiliary switch block typical            | 5 000 000                  |
| • of the contactor with added auxiliary switch block typical                                     | 10 000 000                 |
| reference code acc. to IEC 81346-2                                                               | Q                          |
| Substance Prohibitance (Date)                                                                    | 01.10.2009 00:00:00        |
| <b>Ambient conditions</b>                                                                        |                            |
| installation altitude at height above sea level maximum                                          | 2 000 m                    |
| • ambient temperature during operation                                                           | -25 ... +60 °C             |
| • ambient temperature during storage                                                             | -55 ... +80 °C             |
| <b>Main circuit</b>                                                                              |                            |
| number of poles for main current circuit                                                         | 3                          |
| number of NO contacts for main contacts                                                          | 3                          |
| • operating voltage at AC-3 rated value maximum                                                  | 690 V                      |

|                                                                                                                                                                       |                     |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| <b>operational current</b>                                                                                                                                            |                     |
| <ul style="list-style-type: none"> <li>• at AC-1 at 400 V at ambient temperature 40 °C rated value</li> </ul>                                                         | 18 A                |
| <ul style="list-style-type: none"> <li>• at AC-1 <ul style="list-style-type: none"> <li>— up to 690 V at ambient temperature 40 °C rated value</li> </ul> </li> </ul> | 18 A                |
| <ul style="list-style-type: none"> <li>— up to 690 V at ambient temperature 60 °C rated value</li> </ul>                                                              | 16 A                |
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>                                 | 7 A                 |
| <ul style="list-style-type: none"> <li>— at 500 V rated value</li> </ul>                                                                                              | 6 A                 |
| <ul style="list-style-type: none"> <li>— at 690 V rated value</li> </ul>                                                                                              | 4.9 A               |
| <ul style="list-style-type: none"> <li>• at AC-4 at 400 V rated value</li> </ul>                                                                                      | 6.5 A               |
| <ul style="list-style-type: none"> <li>• at AC-5a up to 690 V rated value</li> </ul>                                                                                  | 15.8 A              |
| <ul style="list-style-type: none"> <li>• at AC-5b up to 400 V rated value</li> </ul>                                                                                  | 5.8 A               |
| <ul style="list-style-type: none"> <li>• at AC-6a <ul style="list-style-type: none"> <li>— up to 230 V for current peak value n=20 rated value</li> </ul> </li> </ul> | 4 A                 |
| <ul style="list-style-type: none"> <li>— up to 400 V for current peak value n=20 rated value</li> </ul>                                                               | 4 A                 |
| <ul style="list-style-type: none"> <li>— up to 500 V for current peak value n=20 rated value</li> </ul>                                                               | 3.8 A               |
| <ul style="list-style-type: none"> <li>— up to 690 V for current peak value n=20 rated value</li> </ul>                                                               | 3.6 A               |
| <ul style="list-style-type: none"> <li>• at AC-6a <ul style="list-style-type: none"> <li>— up to 230 V for current peak value n=30 rated value</li> </ul> </li> </ul> | 2.7 A               |
| <ul style="list-style-type: none"> <li>— up to 400 V for current peak value n=30 rated value</li> </ul>                                                               | 2.7 A               |
| <ul style="list-style-type: none"> <li>— up to 500 V for current peak value n=30 rated value</li> </ul>                                                               | 2.5 A               |
| <ul style="list-style-type: none"> <li>— up to 690 V for current peak value n=30 rated value</li> </ul>                                                               | 2.4 A               |
| minimum cross-section in main circuit at maximum AC-1 rated value                                                                                                     | 2.5 mm <sup>2</sup> |
| <b>operational current for approx. 200000 operating cycles at AC-4</b>                                                                                                |                     |
| <ul style="list-style-type: none"> <li>• at 400 V rated value</li> </ul>                                                                                              | 2.6 A               |
| <ul style="list-style-type: none"> <li>• at 690 V rated value</li> </ul>                                                                                              | 1.8 A               |
| <b>operational current</b>                                                                                                                                            |                     |
| <ul style="list-style-type: none"> <li>• at 1 current path at DC-1 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> </ul> </li> </ul>                | 15 A                |
| <ul style="list-style-type: none"> <li>— at 110 V rated value</li> </ul>                                                                                              | 1.5 A               |
| <ul style="list-style-type: none"> <li>— at 220 V rated value</li> </ul>                                                                                              | 0.6 A               |
| <ul style="list-style-type: none"> <li>— at 440 V rated value</li> </ul>                                                                                              | 0.42 A              |
| <ul style="list-style-type: none"> <li>— at 600 V rated value</li> </ul>                                                                                              | 0.42 A              |
| <ul style="list-style-type: none"> <li>• with 2 current paths in series at DC-1 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> </ul> </li> </ul>   | 15 A                |
| <ul style="list-style-type: none"> <li>— at 110 V rated value</li> </ul>                                                                                              | 8.4 A               |
| <ul style="list-style-type: none"> <li>— at 220 V rated value</li> </ul>                                                                                              | 1.2 A               |
| <ul style="list-style-type: none"> <li>— at 440 V rated value</li> </ul>                                                                                              | 0.6 A               |
| <ul style="list-style-type: none"> <li>— at 600 V rated value</li> </ul>                                                                                              | 0.5 A               |
| <ul style="list-style-type: none"> <li>• with 3 current paths in series at DC-1 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> </ul> </li> </ul>   | 15 A                |
| <ul style="list-style-type: none"> <li>— at 110 V rated value</li> </ul>                                                                                              | 15 A                |
| <ul style="list-style-type: none"> <li>— at 220 V rated value</li> </ul>                                                                                              | 15 A                |
| <ul style="list-style-type: none"> <li>— at 440 V rated value</li> </ul>                                                                                              | 0.9 A               |
| <ul style="list-style-type: none"> <li>— at 600 V rated value</li> </ul>                                                                                              | 0.7 A               |
| <b>operational current</b>                                                                                                                                            |                     |
| <ul style="list-style-type: none"> <li>• at 1 current path at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> </ul> </li> </ul>        | 15 A                |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                           |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>— at 110 V rated value</li> <li>• with 2 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> </ul> </li> <li>• with 3 current paths in series at DC-3 at DC-5 <ul style="list-style-type: none"> <li>— at 24 V rated value</li> <li>— at 110 V rated value</li> <li>— at 220 V rated value</li> <li>— at 440 V rated value</li> <li>— at 600 V rated value</li> </ul> </li> </ul> | 0.1 A<br><br>15 A<br>0.25 A<br><br>15 A<br>15 A<br>1.2 A<br>0.14 A<br>0.14 A                                                                                                                                                                                                                              |
| <b>operating power</b> <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 230 V rated value</li> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul>                                                                                                                                                                                                                                                   | 1.5 kW<br>3 kW<br>3 kW<br>4 kW                                                                                                                                                                                                                                                                            |
| <b>operating power for approx. 200000 operating cycles at AC-4</b> <ul style="list-style-type: none"> <li>• at 400 V rated value</li> <li>• at 690 V rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                    | 1.15 kW<br>1.15 kW                                                                                                                                                                                                                                                                                        |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>• up to 230 V for current peak value n=20 rated value</li> <li>• up to 400 V for current peak value n=20 rated value</li> <li>• up to 500 V for current peak value n=20 rated value</li> <li>• up to 690 V for current peak value n=20 rated value</li> </ul>                                                                                                                                                                  | 1.5 kV·A<br>2.7 kV·A<br>3.3 kV·A<br>4.3 kV·A                                                                                                                                                                                                                                                              |
| <b>operating apparent power at AC-6a</b> <ul style="list-style-type: none"> <li>• up to 230 V for current peak value n=30 rated value</li> <li>• up to 400 V for current peak value n=30 rated value</li> <li>• up to 500 V for current peak value n=30 rated value</li> <li>• up to 690 V for current peak value n=30 rated value</li> </ul>                                                                                                                                                                  | 1 kV·A<br>1.8 kV·A<br>2.2 kV·A<br>2.9 kV·A                                                                                                                                                                                                                                                                |
| <b>short-time withstand current in cold operating state up to 40 °C</b> <ul style="list-style-type: none"> <li>• limited to 1 s switching at zero current maximum</li> <li>• limited to 5 s switching at zero current maximum</li> <li>• limited to 10 s switching at zero current maximum</li> <li>• limited to 30 s switching at zero current maximum</li> <li>• limited to 60 s switching at zero current maximum</li> </ul>                                                                                | 120 A; Use minimum cross-section acc. to AC-1 rated value<br>86 A; Use minimum cross-section acc. to AC-1 rated value<br>67 A; Use minimum cross-section acc. to AC-1 rated value<br>52 A; Use minimum cross-section acc. to AC-1 rated value<br>43 A; Use minimum cross-section acc. to AC-1 rated value |
| <b>no-load switching frequency</b> <ul style="list-style-type: none"> <li>• at AC</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                   | 10 000 1/h                                                                                                                                                                                                                                                                                                |
| <b>operating frequency</b> <ul style="list-style-type: none"> <li>• at AC-1 maximum</li> <li>• at AC-2 maximum</li> <li>• at AC-3 maximum</li> <li>• at AC-4 maximum</li> </ul>                                                                                                                                                                                                                                                                                                                                | 1 000 1/h<br>750 1/h<br>750 1/h<br>250 1/h                                                                                                                                                                                                                                                                |
| <b>Control circuit/ Control</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                           |
| <b>type of voltage of the control supply voltage</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                           | AC                                                                                                                                                                                                                                                                                                        |
| <b>control supply voltage at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> <li>• at 60 Hz rated value</li> </ul>                                                                                                                                                                                                                                                                                                                                                                   | 200 V<br>220 V                                                                                                                                                                                                                                                                                            |
| <b>operating range factor control supply voltage rated value of magnet coil at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                                                                                                         | 0.8 ... 1.1<br>0.85 ... 1.1                                                                                                                                                                                                                                                                               |
| <b>apparent pick-up power of magnet coil at AC</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                                                                                                                                            | 26.4 V·A<br>31.7 V·A                                                                                                                                                                                                                                                                                      |
| <b>inductive power factor with closing power of the coil</b> <ul style="list-style-type: none"> <li>• at 50 Hz</li> <li>• at 60 Hz</li> </ul>                                                                                                                                                                                                                                                                                                                                                                  | 0.81<br>0.81                                                                                                                                                                                                                                                                                              |

|                                                                       |                                                                     |
|-----------------------------------------------------------------------|---------------------------------------------------------------------|
| <b>apparent holding power of magnet coil at AC</b>                    |                                                                     |
| • at 50 Hz                                                            | 4.4 V·A                                                             |
| • at 60 Hz                                                            | 4.8 V·A                                                             |
| <b>inductive power factor with the holding power of the coil</b>      |                                                                     |
| • at 50 Hz                                                            | 0.24                                                                |
| • at 60 Hz                                                            | 0.25                                                                |
| <b>closing delay</b>                                                  |                                                                     |
| • at AC                                                               | 9 ... 35 ms                                                         |
| <b>opening delay</b>                                                  |                                                                     |
| • at AC                                                               | 3.5 ... 14 ms                                                       |
| <b>arcing time</b>                                                    | 10 ... 15 ms                                                        |
| <b>control version of the switch operating mechanism</b>              | Standard A1 - A2                                                    |
| <b>Auxiliary circuit</b>                                              |                                                                     |
| number of NO contacts for auxiliary contacts<br>instantaneous contact | 1                                                                   |
| operational current at AC-12 maximum                                  | 10 A                                                                |
| <b>operational current at AC-15</b>                                   |                                                                     |
| • at 230 V rated value                                                | 10 A                                                                |
| • at 400 V rated value                                                | 3 A                                                                 |
| • at 500 V rated value                                                | 2 A                                                                 |
| • at 690 V rated value                                                | 1 A                                                                 |
| <b>operational current at DC-12</b>                                   |                                                                     |
| • at 24 V rated value                                                 | 10 A                                                                |
| • at 48 V rated value                                                 | 6 A                                                                 |
| • at 60 V rated value                                                 | 6 A                                                                 |
| • at 110 V rated value                                                | 3 A                                                                 |
| • at 125 V rated value                                                | 2 A                                                                 |
| • at 220 V rated value                                                | 1 A                                                                 |
| • at 600 V rated value                                                | 0.15 A                                                              |
| <b>operational current at DC-13</b>                                   |                                                                     |
| • at 24 V rated value                                                 | 10 A                                                                |
| • at 48 V rated value                                                 | 2 A                                                                 |
| • at 60 V rated value                                                 | 2 A                                                                 |
| • at 110 V rated value                                                | 1 A                                                                 |
| • at 125 V rated value                                                | 0.9 A                                                               |
| • at 220 V rated value                                                | 0.3 A                                                               |
| • at 600 V rated value                                                | 0.1 A                                                               |
| <b>contact reliability of auxiliary contacts</b>                      | 1 faulty switching per 100 million (17 V, 1 mA)                     |
| <b>UL/CSA ratings</b>                                                 |                                                                     |
| <b>full-load current (FLA) for 3-phase AC motor</b>                   |                                                                     |
| • at 480 V rated value                                                | 4.8 A                                                               |
| • at 600 V rated value                                                | 6.1 A                                                               |
| <b>yielded mechanical performance [hp]</b>                            |                                                                     |
| • for single-phase AC motor                                           |                                                                     |
| — at 110/120 V rated value                                            | 0.25 hp                                                             |
| — at 230 V rated value                                                | 0.75 hp                                                             |
| • for 3-phase AC motor                                                |                                                                     |
| — at 200/208 V rated value                                            | 1.5 hp                                                              |
| — at 220/230 V rated value                                            | 2 hp                                                                |
| — at 460/480 V rated value                                            | 3 hp                                                                |
| — at 575/600 V rated value                                            | 5 hp                                                                |
| <b>contact rating of auxiliary contacts according to UL</b>           | A600 / Q600                                                         |
| <b>Short-circuit protection</b>                                       |                                                                     |
| <b>design of the fuse link</b>                                        |                                                                     |
| • for short-circuit protection of the main circuit                    |                                                                     |
| — with type of coordination 1 required                                | gG: 35A (690V,100kA), aM: 20A (690V,100kA), BS88: 35A (415V,80kA)   |
| — with type of assignment 2 required                                  | gG: 20A (690V,100kA), aM: 16A (690V, 100kA), BS88: 20A (415V, 80kA) |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>for short-circuit protection of the auxiliary switch required</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                 | gG: 10 A (500 V, 1 kA)                                                                                                                                                                                 |
| <b>Installation/ mounting/ dimensions</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                                                                                        |
| <b>mounting position</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface                                                                   |
| <b>fastening method</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715                                                                                                                 |
| <ul style="list-style-type: none"> <li>side-by-side mounting</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                         | Yes                                                                                                                                                                                                    |
| <b>height</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 58 mm                                                                                                                                                                                                  |
| <b>width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 45 mm                                                                                                                                                                                                  |
| <b>depth</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 73 mm                                                                                                                                                                                                  |
| <b>required spacing</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>with side-by-side mounting <ul style="list-style-type: none"> <li>forwards</li> <li>upwards</li> <li>downwards</li> <li>at the side</li> </ul> </li> <li>for grounded parts <ul style="list-style-type: none"> <li>forwards</li> <li>upwards</li> <li>at the side</li> <li>downwards</li> </ul> </li> <li>for live parts <ul style="list-style-type: none"> <li>forwards</li> <li>upwards</li> <li>downwards</li> <li>at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                                                                                          |
| <b>Connections/ Terminals</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                                                                                                                                        |
| <b>type of electrical connection</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>for main current circuit</li> <li>for auxiliary and control circuit</li> <li>at contactor for auxiliary contacts</li> <li>of magnet coil</li> </ul>                                                                                                                                                                                                                                                                                                      | screw-type terminals<br>screw-type terminals<br>Screw-type terminals<br>Screw-type terminals                                                                                                           |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>for main contacts <ul style="list-style-type: none"> <li>solid</li> <li>solid or stranded</li> <li>finely stranded with core end processing</li> </ul> </li> <li>at AWG cables for main contacts</li> </ul>                                                                                                                                                                                                                                              | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²<br>2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²<br>2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)<br>2x (20 ... 16), 2x (18 ... 14), 2x 12 |
| <b>connectable conductor cross-section for main contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>solid</li> <li>stranded</li> <li>finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                     | 0.5 ... 4 mm²<br>0.5 ... 4 mm²<br>0.5 ... 2.5 mm²                                                                                                                                                      |
| <b>connectable conductor cross-section for auxiliary contacts</b>                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>solid or stranded</li> <li>finely stranded with core end processing</li> </ul>                                                                                                                                                                                                                                                                                                                                                                           | 0.5 ... 4 mm²<br>0.5 ... 2.5 mm²                                                                                                                                                                       |
| <b>type of connectable conductor cross-sections</b>                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                        |
| <ul style="list-style-type: none"> <li>for auxiliary contacts <ul style="list-style-type: none"> <li>solid or stranded</li> <li>finely stranded with core end processing</li> </ul> </li> <li>at AWG cables for auxiliary contacts</li> </ul>                                                                                                                                                                                                                                                   | 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²), 2x 4 mm²<br>2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)<br>2x (20 ... 16), 2x (18 ... 14), 2x 12                                                          |
| <ul style="list-style-type: none"> <li>AWG number as coded connectable conductor cross section for main contacts</li> <li>AWG number as coded connectable conductor cross section for auxiliary contacts</li> </ul>                                                                                                                                                                                                                                                                             | 20 ... 12<br>20 ... 12                                                                                                                                                                                 |
| <b>Safety related data</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                        |
| B10 value with high demand rate acc. to SN 31920                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1 000 000                                                                                                                                                                                              |

|                                                                           |                                                  |
|---------------------------------------------------------------------------|--------------------------------------------------|
| <b>proportion of dangerous failures</b>                                   |                                                  |
| • with low demand rate acc. to SN 31920                                   | 40 %                                             |
| • with high demand rate acc. to SN 31920                                  | 73 %                                             |
| failure rate [FIT] with low demand rate acc. to SN 31920                  | 100 FIT                                          |
| <b>product function</b>                                                   |                                                  |
| • mirror contact acc. to IEC 60947-4-1                                    | Yes; with 3RH29                                  |
| <b>T1 value for proof test interval or service life acc. to IEC 61508</b> | 20 y                                             |
| <b>protection class IP on the front acc. to IEC 60529</b>                 | IP20                                             |
| <b>touch protection on the front acc. to IEC 60529</b>                    | finger-safe, for vertical contact from the front |
| suitability for use safety-related switching OFF                          | Yes                                              |
| <b>Certificates/ approvals</b>                                            |                                                  |
| <b>General Product Approval</b>                                           | <b>EMC</b>                                       |



[KC](#)



|                                  |                                                                                               |                                                                                                       |
|----------------------------------|-----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| <b>Declaration of Conformity</b> | <b>Test Certificates</b>                                                                      | <b>Marine / Shipping</b>                                                                              |
| <a href="#">Miscellaneous</a>    | <br>EG-Konf. | <a href="#">Type Test Certificates/Test Report</a>                                                    |
|                                  |                                                                                               | <a href="#">Special Test Certificate</a>                                                              |
|                                  |                                                                                               | <br>ABS            |
|                                  |                                                                                               | <br>BUREAU VERITAS |
| <b>Marine / Shipping</b>         | <b>other</b>                                                                                  |                                                                                                       |



[Confirmation](#)

|                                                                                     |
|-------------------------------------------------------------------------------------|
| <b>other</b>                                                                        |
|  |
| <a href="#">Confirmation</a>                                                        |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Further information</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Information- and Downloadcenter (Catalogs, Brochures,...)</b><br><a href="https://www.siemens.com/ic10">https://www.siemens.com/ic10</a><br><b>Industry Mall (Online ordering system)</b><br><a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2015-1AN61">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2015-1AN61</a><br><b>Cax online generator</b><br><a href="http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3RT2015-1AN61">http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&amp;mlfb=3RT2015-1AN61</a><br><b>Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)</b><br><a href="https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1AN61">https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1AN61</a><br><b>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)</b><br><a href="http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2015-1AN61&amp;lang=en">http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2015-1AN61&amp;lang=en</a><br><b>Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current</b><br><a href="https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1AN61/char">https://support.industry.siemens.com/cs/ww/en/ps/3RT2015-1AN61/char</a><br><b>Further characteristics (e.g. electrical endurance, switching frequency)</b><br><a href="http://www.automation.siemens.com/bilddb/index.aspx?view=Search&amp;mlfb=3RT2015-1AN61&amp;objecttype=14&amp;gridview=view1">http://www.automation.siemens.com/bilddb/index.aspx?view=Search&amp;mlfb=3RT2015-1AN61&amp;objecttype=14&amp;gridview=view1</a> |





