

NOTES:

1. MATERIALS AND FINISHES:

BODY & COUPLING NUT - BRASS (ASTM-B16 H02, C36000), NICKEL PLATING
CONTACT PIN - BRASS, GOLD PLATING
INSULATOR - PTFE PER ASTM D 1710 OR EQUIV.

2. ELECTRICAL:

A. IMPEDANCE: 50 OHM
B. FREQUENCY RANGE: DC - 11 GHz

3. MECHANICAL:




A. TEMPERATURE RANGE: -65° C TO +165° C

4. PACKAGING:

A. QUANTITY: SINGLE PACK
B. MARKING: BAG TO BE MARKED
*AMPHENOL, 31-6145, AND DATE CODE

5. CRIMPED CONTACT PIN = HEX CRIMP SIZE .068 IN

31-6145		REVISIONS			
DRAWING NO.	REV	DESCRIPTION	DATE	ECO	APPR
THIRD ANGLE PROJ. 	A	RELEASE TO MFG.	8/29/06	46221	CPM/



RECOMMENDED
CABLE STRIPPING DIM'S

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

MATERIAL	DRAWN C. McGRATH	DATE 4/12/05
	ENGINEER □. BARTHELMES	DATE 4/12/05
	APPROVED □. BARTHELMES	DATE 8/25/06
REFERENCE		

TITLE
TNC DIRECT SOLDER PLUG
(FOR .141" SEMI RIGID
CABLE)

Amphenol
Amphenol Corporation
RF/Microwave Operations
Danbury, Conn. U.S.A. 06810

SCALE: 2:1	SHEET	OF	ISSUE A
------------	-------	----	------------

CAD FILE H:\DEPT611\TNC\031\ASSY\6145

CODE ID
74868

DWG SIZE
B

DRAWING NO.
31-6145