

Part Number: 1210230571

Product Description: mPm DIN Valve Connector, Form B-10mm, PG9 Internal Threads, 2 Pole, H12 Ground Position, Black, Nitrile Profile Gasket and Screw, Mounted,

Bulk Pack

Series Number: 121023

Product Category: Circular Industrial

Connectors

Status: Active

Engineering Number: C62209N21

Documents & Resources

Drawings

Drawing 1210230571_sd.pdf

Specifications

Packaging Specification PK-121023-C62-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | <u> </u> |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per ED/30/2017 (7 July 2017) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

| Status | Active |
|----------------|---|
| Category | Circular Industrial Connectors |
| Series | 121023 |
| Description | mPm DIN Valve Connector, Form B- 10mm, PG9 Internal Threads, 2 Pole, H12 Ground Position, Black, Nitrile Profile Gasket and Screw, Mounted, Bulk Pack |
| IP Rating | IP65 |
| Product Family | mPm DIN Valve Connectors |
| Product Name | mPm |
| Туре | Field Attachable Connector |
| UPC | 883906322045 |

Electrical

| Current - Maximum per Contact | 16.0A |
|-------------------------------|-------------------|
| Voltage - Maximum | 250V AC / 300V DC |

Physical

| Cable Diameter | 6.00-8.00mm (.236315") |
|---------------------------|------------------------|
| Coupling Type | Internal Thread |
| Diagnostics / LEDs | No |
| Diagnostics Port | No |
| Form | B - 10mm |
| Gender | N/A |
| Keyway | None |
| Material - Connector Body | Polypropylene |
| Material - Contact | Brass |
| Material - Coupling Nut | N/A |
| Material - Plating Mating | Silver |
| Net Weight | 20.213/g |
| Orientation | 90° Angle |

| Pitch - Mating Interface | 10.00mm |
|-------------------------------|----------------|
| Poles | 2 |
| Temperature Range - Operating | -40°C to +90°C |
| Wire Size (AWG) | 16 |

This document was generated on Sep 16, 2024