




Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Header**

Connector & Housing Type: **Receptacle**

Connector System: **Wire-to-Board**

Number of Positions: **8**

Centerline (Pitch): **6.35 mm [.25 in]**

Features

Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	8
PCB Mount Orientation	Right Angle
Number of Power Positions	8
Number of Rows	1

Electrical Characteristics

Operating Voltage	600 VAC
-------------------	---------

Contact Features

Multiple Contact Types	Without
------------------------	---------



Contact Layout	Inline
Contact Mating Area Plating Material	Tin
Contact Current Rating (Max)	12 A
Contact Retention Within Housing	Without
Contact Type	Socket
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	3.81 – 5.08 µm[150 – 200 µin]

Termination Features

Termination Post & Tail Length	3.7 mm[.146 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	With
PCB Mount Retention Type	Mounting Hole
Mating Retention Type	Positive Lock
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	6.35 mm[.25 in]
Housing Color	Natural
Housing Material	Nylon

Dimensions

Connector Height	9.14 mm
PCB Thickness (Recommended)	3.18 mm[.125 in]
Product Width	17.27 mm
Product Length	69.27 mm

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------



Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

CSA Rating	Certified, LR 7189
UL Rating	Recognized
Compatible With Agency/Standards Products	CSA, UL, VDE
Compatible With Approved Standards Products	UL E28476
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire

Packaging Features

Packaging Quantity	140
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>



Compatible Parts

 TE Part # 1-350589-0 STR/REL CLAMP NATL	 TE Part # 640582-1 08P UMNL PLUG HSG	 TE Part # 350811-1 STR/REL CLAMP	 TE Part # 826851-3 8P UN-MNL BU SOCK
 TE Part # 643314-1 08P UMNL STR/REL	 TE Part # 1969815-1 08P UMNL HDR ASSY R/A, PIN V0 GW	 TE Part # 1969816-1 08P UMNL HDR ASSY R/A, SCKT V0 GW	 TE Part # 643314-2 08P UMNL STR/REL HSG

Also in the Series | Universal MATE-N-LOK

 Circular Power Connectors(2)	 Connector Caps & Covers(34)	 Connector Contacts(209)	 Connector Hardware(12)
 Connector Seals & Cavity Plugs(27)	 Connector Strain Relief(7)	 Insertion & Extraction Tools(4)	 Rectangular Connector Housings(1)



[Rectangular Power Connectors\(670\)](#)



[Standard Circular Connectors\(1\)](#)

Customers Also Bought



TE Part #2013595-3
[INDUSTRIAL MINI I/O PLUG KIT D1 GRAY](#)



TE Part #2-1419128-9
[OJE-SS-105HM,000](#)



TE Part #2-2176049-9
[RLP73K 1E R75 1% 1K RL](#)



TE Part #1-350944-0
[04P UMNL HDR ASSY R/A 94VO](#)




TE Part #643416-1
[04P UMNL HDR ASSY POL 94VO](#)




TE Part #2-1825910-2
[FSM12JH=6MM TACT SWITCH, HIGH TEMP](#)



TE Part #2-1676481-1
[CPF 0603 36R 0.1% 25PPM 1K RL](#)



TE Part #4-2176326-6
[CRGP 0603 56K 1%](#)



TE Part #5-2176422-8
[TLRP 2512 3.0W R020 1% 50PPM 4K RL](#)

Documents

Product Drawings

[08P UMNL HDR ASSY R/A 94VO](#)

English

CAD Files

[3D PDF](#)

[3D](#)

[Customer View Model](#)

[ENG_CVM_CVM_643236-1_H.2d_dxf.zip](#)



English

Customer View Model

[ENG_CVM_CVM_643236-1_H.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_643236-1_H.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_643236-1_D.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_643236-1_D.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_643236-1_D.2d_dxf.zip](#)

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[SOFT_SHELL_PIN_SOCKET_CONNECTORS_STANDARD_DENSITY](#)

English

Product Specifications

[Application Specification](#)

English

Instruction Sheets

[Instruction Sheet \(U.S.\)](#)

English

Agency Approvals

[UL](#)

English