



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Primary Product Material: **Silicone**

Primary Product Color: **Gray**

Operating Temperature (Max): 65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C, 140 °C, 150 °C, 155 °C, 170 °C, 180 °C [149 °F, 158 °F, 167 °F, 176 °F, 185 °F, 194 °F, 212 °F, 221 °F, 230 °F, 248 °F, 257 °F, 266 °F, 284 °F, 302 °F, 311 °F, 338 °F, 356 °F]

Operating Temperature Range: -40 – 180 °C [-40 – 356 °F]

Features

Body Features

Primary Product Material	Silicone
Primary Product Color	Gray

Usage Conditions

Operating Temperature (Max)	65 °C, 70 °C, 75 °C, 80 °C, 85 °C, 90 °C, 100 °C, 105 °C, 110 °C, 120 °C, 125 °C, 130 °C, 140 °C, 150 °C, 155 °C, 170 °C, 180 °C[149 °F][158 °F][167 °F][176 °F][185 °F][194 °F][212 °F][221 °F][230 °F][248 °F][257 °F][266 °F][284 °F][302 °F][311 °F][338 °F][356 °F]
Operating Temperature Range	-40 – 180 °C[-40 – 356 °F]

Packaging Features

Packaging Quantity	5000
Packaging Method	Bag

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241)



Candidate List Declared Against: JUN 2020
(209)
Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 344106-1
18W EMS.REC.HSG.ASSY.

Customers Also Bought

TE Part #9-6437287-8
SUPER SEAL 26POS CAP ASSY H AU

TE Part #52955-1
TERMINAL,PG SPR SPD 16-14 6

TE Part #344265-1
6 WAY TAB HSG.- BLACK ECONO


TE Part #1-1718485-3
CARRIER FOF RECEPT INSERTS 36 POS





TE Part #175104-2

MULTILOCK, RECEPTACLE AND TAB



TE Part #3-1447221-3

S/S REC CONTACT ASSY, AU, 0.75~1.25




TE Part #969044-1

SPT A REC 6.3 Contact SWS Sn



TE Part #936251-2

090 SLD 3P PLUG ASSY BLACK



TE Part #174929-1

070 MLC W-W CAP HSG 4P NATURAL

Documents

Product Drawings

ECON 3 LC PLUG SILIC

English

CAD Files

Customer View Model

ENG_CVM_348461-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_348461-1_A.3d_stp.zip

English

Customer View Model

ENG_CVM_348461-1_A.2d_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Product Datasheet

English