Data Sheet

HUBER+SUHNER Excellence in Connectivity Solutions

Coaxial Panel Connector 23_4310-50-0-16/003_-

Description

Straight panel receptacle jack, flange mount

Interface standards IEC 61169-54



Technical Data

Electrical Data

Impedance 50 Ω Interface frequency max. 12 GHz

Mechanical Data

Number of matings 100
Weight 0.064381 kg

Environmental Data

Operating temperature -55 °C to 90 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium / Brass	Silver Plating
Outer contact	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Gasket	VMQ (Silicone rubber)	

Related Documents

Outline drawing DOU-00288045
Catalogue drawing DCA-00292638

Ordering Information

Tray package 23_4310-50-0-16/003_-Y

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical specifications and/or the fitness for any particular purpose. The facts and figures contained herein are carefully compiled to the best of our knowledge, but they are intended for general information purposes only.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER: 23_4310-50-0-16/003_-Y