

D1NS4

40V 1A


FEATURES

- Tj150°C
- PRRSM avalanche guaranteed
- 5 mm pitch mounting applicable

APPLICATION

- Switching power supply
- DC/DC converter
- Home Appliances, Office Equipment
- Telecommunication

OUTLINE DIMENSIONS



RATINGS

● Absolute Maximum Ratings (If not specified Tl=25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	Tstg		-55~150	°C
Operating Junction Temperature	Tj		150	°C
Maximum Reverse Voltage	VRM		40	V
Repetitive Peak Surge Reverse Voltage	VRRSM	Pulse width 0.5ms, duty 1/40	45	V
Average Rectified Forward Current	IO	50Hz sine wave, Ta=59°C	1	A
Peak Surge Forward Current	IFSM	50Hz sine wave, Non-repetitive 1 cycle peak value, Tj=125 °C	30	A
Repetitive Peak Surge Reverse Power	PRRSM	Pulse width 10 μ s, Tj=25°C	60	W

● Electrical Characteristics (If not specified Tl=25°C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	VF	IF=1A, Pulse measurement	Max.0.55	V
Reverse Current	IR	VR=40V, Pulse measurement	Max.0.8	mA
Junction Capacitance	Cj	f=1MHz, VR=10V	Typ.50	pF
Thermal Resistance	θ jl	junction to lead	Max.10	°C/W
	θ ja	junction to ambient, On P.C.B.	Max.113	


D1NS4

Forward Voltage




D1NS4

Junction Capacitance




D1NS4

Reverse Current




D1NS4

Reverse Power Dissipation




$T_j = 150^\circ\text{C}$



D1NS4

Forward Power Dissipation




$T_j = 150^\circ\text{C}$




D1NS4

Derating Curve




$V_R = 20\text{V}$



D1NS4

Peak Surge Forward Capability



SBD Repetitive Surge Reverse Power Derating Curve

