




REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	RELEASED PER ECR-15-009171	25JUN15	O.C	D.Z


- 1

MATERIAL: PHOSPHOR BRONZE.
- 2


FINISH: PRE-TIN.
- 3 DESIGNED FOR USE IN HOUSINGS 1969442-() OR 1744417-().
- 4 CONTACTS COATED WITH ANTI-FRETTING LUBRICANT.
- 5 CONTACT IS RoHS COMPLIANT.
- 6 WIRE RANGE: 0.13~0.36mm2 [26-22 AWG] STRANDED.
7. INSULATION RANGE: 1.30~1.91



SECTION A-A



SECTION B-B



SECTION C-C

2232905-1
PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN OTTO CHEN 25JUN15	TE TE Connectivity			
DIMENSIONS:		CHK DANIEL. Z 26JUN15				
mm		APVD DANIEL. Z 26JUN15	NAME			
		PRODUCT SPEC	LOW INSERTION FORCE CONTACT, ECONOMY POWER 2.5, RECEPTACLE			
		108-2418				
		APPLICATION SPEC				
MATERIAL		114-13315	SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
		WEIGHT	A200779	C-2232905		-
		Customer Drawing	SCALE	N/A	SHEET 1 OF 1	REV A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[2232905-1](#) [2232905-1 \(Mouser Reel\)](#)