




This document is the property of Amphenol Corporation and is delivered on the express condition that it is not to be disclosed, reproduced or used, in whole or in part, for manufacture or sale by anyone other than Amphenol Corporation without its prior consent, & that no right is granted to disclose or to use any information in this document.



Customer Drawing

DIM.S SHELL	A	B	C	Pitch
9	30.70	16.40	25.00	2.74
15	39.00	24.80	33.30	2.74
25	52.90	38.50	47.00	2.76
37	69.20	54.90	63.50	2.76

REVISIONS

SYM	ECN	DESCRIPTION	DATE	APPROVED
1	HK--	First Release Drawing	10/22/08	IP

D-SUB TECHNICAL DATA

SHELL : Steel 2.5um(100u") min tin over 1.25um(50u") min nickel
BODY : Glass filled thermoplastic.
Flame retardant to UL94 V-0 Color Black
CONTACTS : Brass
0.1um(4u") min gold over 1.25um(50u") min nickel
REAR NUT : Brass,100u" min tin over 50u" min nickel.
ELECTRICAL : Voltage rating :300 V RMS at 50 Hz
Current rating 7.5A.
Insulation resistance >5000 M Ohms
Withstanding voltage 1000V AC for one minute
Contact resistance 20 mOhms max.
CLIMATIC : Temperature range -55 °C up to +125°C
Damp heat 21 days(40 °C-95% HR)
MARKING : Amphenol---(Series No.)
Commercial reference
Manufacturing date

PRODUCT CODE

L 77D X H XX S

L: RoHS Compliance

Contact type:
S: Socket

77D: tinned shell
for receptacle

Configuration: 09,15,25,37

Shell Size :E,A,B,C

H:Rear insert 4-40

UNLESS OTHERWISE SPECIFIED TOLERANCES		APPROVAL	DATE
U.S.	METRIC	DRAWN	Christine.cui
.X +/-	0.50	CHECKED	lik.wang
.XX +/-	0.30	CHECKED	
.XXX +/-	0.20		
FRACTIONS +/-	5°		
ANGLES +/-			
FOR MATERIALS AND FINISHES SEE NOTES		DRAWING FILE :	
REMOVE SHARP EDGES		ANGLE OF PROJECTION	
DIMENSIONS		U.S. INCHES	
METRIC MM		SCALE	

5	Amphenol		
19	Amphenol East Asia Limited		
6	TITLE		
	Machined contacts connector, D series		
SIZE	DRAWING NO.		REV.
A4	C L77DXHXXS		1
SCALE	NONE	SHEET 1 OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[L77DAH15S](#) [L77DBH25S](#) [L77DEH09S](#) [L77DCH37S](#)